

WhereScape®

WhereScape® RED

Installation Manual

Version 8.6.1.0 | December 2020

Table of Contents

Overview	5
WhereScape Forum	5
How to use this Manual	5
Installing WhereScape RED	7
Installing WhereScape RED from the Command Line	11
Adding Your License	12
Checking your Windows Version	16
Checking ODBC Drivers	18
Creating an ODBC Connection	20
SQL Server Installation and Configuration	23
Introduction	23
Problem Solving	23
Installing RED for SQL Server	23
SQL Server Database and Login Setup	24
SQL Server Database	24
SQL Server Login Setup	24
Server Level Permissions	24
Database Permissions	24
Configuring a SQL Server Metadata Connection (DSN)	25
Creating a Metadata Repository for SQL Server	29
SQL Server Quick Start	30
SQL Server Quick Application	31
Windows Command Line Invocation	33
Teradata Installation and Configuration	35
Introduction	35
Problem Solving	35
Installing RED for Teradata	36
Creating a Teradata Environment	36
Configuring a Teradata Metadata Connection (DSN)	37
Creating a Metadata Repository for Teradata	40
Oracle Installation and Configuration	43
Introduction	43
Problem Solving	43
Installing RED for Oracle	44
Creating an Oracle User	44
Creating Oracle Individual Users	46
Configuring an Oracle Metadata Connection (DSN)	49

Validating Oracle User Privileges	51
Creating a Metadata Repository for Oracle.....	54
Insufficient privileges on procedure compile (Oracle)	56
Tutorial Data	57
Creating Tutorial Data	57
Validating Tutorial Data	58
Applications	60
Loading an Application	60
Backing Up the Metadata before Loading Applications.....	62
Application Load Process.....	62
Metadata Options.....	66
Data Warehouse Options.....	68
Data Warehouse Table/View Options.....	69
Adding Connections and Targets	71
Creating and Loading Applications from the Command Line	73
Setup Administrator Process Exit Codes	74
Changing the Application Directory	76
Listing Applications.....	78
Testing Applications	78
XML Options File for Application Loads	78
Upgrading WhereScape RED.....	82
Upgrading RED	82
Oracle Invalid Procedures.....	83
Checking the Unix Connection.....	85
Testing an ODBC Source	86
Validating a Meta Repository.....	88
Oracle Invalid Procedures.....	88
Validating a Metadata Repository using the Command Line	89
Scheduler Installation and Configuration	91
Diagram Overview of RED and Scheduler Database Access.....	91
Installing a Windows Scheduler.....	94
Installing a UNIX/Linux Scheduler.....	99
Unix Scheduler setup for Hadoop loads using Oracle's Big Data Connectors.....	105
Maintaining the Windows Scheduler	106
BDA	108
Prerequisites.....	108
BDA Diagram Overview.....	108
How to set up BDA	110
Adding JDBC Drivers.....	112
Testing the BDA Setup	113

Configuring Kerberos for a secure use with BDA.....	114
Troubleshooting	118
Languages	119
Loading Languages	119
Creating a Language File	119
Changing the Languages Directory	121
Tools	123
Start/Stop logging	123
RED Command Line Interface	125
RED Setup Administrator Command Line (adm.exe).....	125
RED Setup Administrator Command Line Arguments	126
Quick Application	127
Quick Repository.....	127
Quick Language.....	128
Quick Validate.....	128
Quick Tutorial.....	129
Deploy Application	129
Windows Scheduler	129
RED Client Command Line (med.exe)	130
RED Client Command Line Arguments	131
Batch Documentation Creation.....	132
Batch Deployment Application Creation	133
New Metadata Repository Start up Task Creation.....	134

Overview

WhereScape RED provides an environment to facilitate the rapid production of prototype data warehouse analysis areas. It also provides the functionality to move that prototype into a production environment and support the day-to-day running of a data warehouse.

The Installation and Administration Guide provides the information needed to:

- Install the WhereScape RED software.
- Validate the various software components required by WhereScape RED.
- Install the WhereScape RED metadata.
- Install a Scheduler.
- Optionally install third-party data warehouse applications.

Note:

The software described in this manual is furnished under a license agreement and may be used only in accordance with the terms of the agreement.

WhereScape Forum

A web forum is available at www.wherescape.com. This forum contains information on the latest version, and bug reports that may be relevant for installation. In addition, the WhereScape Blog is available at www.wherescape.com which may provide additional information.

How to use this Manual

WhereScape RED is designed to build data warehouse analysis areas within a database environment. The installation and configuration process are very rarely a simple task as it involves several layered products external to WhereScape RED. For the more complex cases, several hours or days should be set aside to complete this task.

Therefore, it is important that the reader begins the installation process with the correct expectations. Highlighted below are the major steps in the installation and setup of WhereScape RED. In many environments some of these steps will have been completed independently of the installation process or may need to be completed by a third party.

Note:

This document does not cover the creation and configuration of the database required to run the data warehouse. It does not cover the procedures required to create and maintain database users; nor does it cover the installation of the database client software. Refer to the database vendor manuals for assistance.

The **Installation and Configuration** chapters provide a logical outline for the installation and setup of WhereScape RED for the following databases:

- For SQL Server, refer to [SQL Server Installation and Configuration](#) for details.
- For Teradata, refer to [Teradata Installation and Configuration](#) for details.
- For Oracle, refer to [Oracle Installation and Configuration](#) for details.

The rest of the manual deals with the following topics:

- [Tutorial Data](#) for creating and validating the tutorial data.
- [Applications](#) for loading the data warehouse applications.
- [Upgrading](#) for upgrading WhereScape RED.
- [Unix Connection](#) for checking the Unix connection.
- [Test ODBC Source](#) for testing an ODBC source.

- [Validate Repository](#) for validating a meta repository.
- [Maintain Scheduler](#) for maintaining the Windows scheduler.
- [Languages](#) for creating and loading language files.

Installing WhereScape RED

Complete the following procedure to install the WhereScape RED software:


Notes:

Before you begin the install process:

- Stop any WhereScape RED schedulers running on the computer.
- Close any other applications that are running.
- Ensure that you have installed the following Microsoft software packages:

Package	File Name	File Size (KB)
Visual C++ Redistributable for Visual Studio 2019 (x64)	vc_redist.x64.exe	14,708
Visual C++ Redistributable for Visual Studio 2019 (x86)	vc_redist.x86.exe	14,028
.NET Framework 4.6.1	NDP461-KB3102436-x86-x64-AllOS-ENU.exe	66,095
.NET Framework 4.6.1 (web installer)	NDP461-KB3102438.exe	1,391

1. Double-click the RED_xxxx.exe file (For example: the downloaded file for version 6.8.4.0, would be RED_68400.exe).
The **WhereScape RED Setup Wizard** window is displayed.




2. Click **Next** to continue with the installation.

Note:

The installer checks for certain prerequisites that are needed to run some components of RED. If any of the prerequisites are missing, clicking **Next** takes you to the list of required prerequisites and you need to install them. To skip this step and jump directly to the installation of RED, click **Finish**.

The **WhereScape RED Setup End-User License Agreement** window is displayed. Read the license terms.




3. Select the **I accept the terms in the License Agreement** option and click **Next** to continue.

Note:


If you do not accept the license agreement, you cannot continue with the installation.

4. The **Select Installation Folder** window is displayed, showing the directory where the WhereScape RED software will be installed. To change the directory, click **Browse...** to navigate to the required **Installation Folder** and then click **Next** to continue.




5. The **Ready to Install** window is displayed, giving you the opportunity to go back and change any of the information you have entered so far.


Click **Install** to install the WhereScape RED software.



6. The **Installing WhereScape RED** window is displayed, showing you the progress of the installation.



7. A window is displayed after completing the installation. Click **Finish** to exit and **Launch the Setup Administrator**.

**Note:**

If a scheduler was running or a program was open (when doing an upgrade), a prompt displays advising you that a reboot is required to finish the installation.

Installing WhereScape RED from the Command Line

It is possible to install WhereScape RED from the command line and specify a custom installation directory, using the APPDIR parameter by running a batch file.

This process can be used for all metadata database types where the exe file is configured to copy the APPDIR property into all other relevant properties.

Note:

Command Line installations will only work if the relevant version has not yet been previously installed. If the same version has already been installed, it must always be removed first.

Example

The following is an example script that loads RED with full verbose logging:

```
@echo off
cd c:\users\user\downloads\
"RED_68500.exe" APPDIR="c:\WhereScape68500\" ALLUSERS=1 RebootYesNo="No" Reboot="Suppress"
/qn+ /L*vx "c:\WhereScape\log.txt"
exit
```

Please refer to Caphyon's Advanced Installer [documentation](#) for more details about command-line options.

To install versions of WhereScape RED older than 6.8.3.4 using the command line, please use the following script instead:

```
@echo off
cd c:\users\user\downloads\
msiexec /i "RED_68300.msi" APPDIR="C:\WhereScape68500\" ALLUSERS=1 RebootYesNo="No"
Reboot="Suppress" /qn+ /L*vx "c:\WhereScape\log.txt"
exit
```

Please refer to [Microsoft Documentation](#) for more details about Msiexec command-line options.


Adding Your License

Tip:


WhereScape RED requires a valid licensee and license key. This information and the key are normally supplied in a separate email.

To add your license:

1. In WhereScape's **Setup Administrator**, click the **Computer Setup** tab and then click **WhereScape RED License**.



The Welcome to WhereScape RED License screen is displayed.



WhereScape®
RED

WELCOME TO WHERESCAPE RED

Please enter the "Licensed To" and "License Key" information in the boxes below.
You will then be asked to confirm your license information before the key is accepted.

If you do not know your license information, please contact your site administrator or WhereScape Software Limited sales contact.

Licensed To:


License Key:

This screen enables you to enter your license information.

Once validated, the license information is stored in the registry and validated by the WhereScape RED program on start up.

2. Enter the required information in the license fields and then click **OK**.

The example below shows the entry of an evaluation license and key.



WhereScape®
RED

WELCOME TO WHERESCAPE RED

Please enter the "Licensed To" and "License Key" information in the boxes below.
You will then be asked to confirm your license information before the key is accepted.

If you do not know your license information, please contact your site administrator or WhereScape, Inc. sales contact.

Licensed To:

License Key:

The license type window is displayed:

Accept WhereScape License Terms and Conditions

Usage	
Licensed Metadata Database Type(s)	SQL Server, Oracle, DB2, Teradata
Licensed Target Database Type(s)	SQL Server, Oracle, DB2, Teradata, Netezza, Greenplum, PDW, Hive, Custom
Licensed Model Type(s)	Star Schema, Data Store, 3NF, Data Vault
Licensed Users	Unlimited users
Licensed Usage Type	WhereScape Employee
Restriction(s)	None
Expiry	31 Dec 2020
Licensed Custom Target Database Type	Snowflake

If this is the same as the usage defined in your Licensee Fee invoice and you accept the conditions below (or you have a signed WhereScape agreement) please click ACCEPT.
If this is not the same as the usage defined in your Licensee Fee invoice please click DECLINE and request an updated key from your WhereScape sales contact.

This Agreement is made:

between **WhereScape, Inc., a Delaware corporation (the "Company")**
and **You (the "Licensee")**

General Terms

1. Definitions

1.1 In this Agreement, unless the context otherwise requires

Confidential Information means all information exchanged between the parties to this Agreement, whether in writing, electronically or orally, including terms of this Agreement, but does not include information which is, or becomes publicly available other than through unauthorized disclosure by the other party. In the case of the Company, the term Confidential Information includes the Software and the Documentation;

Control means, in relation to a party, the power to:

(a) manage, directly or indirectly, the operation of the business; or
(b) control, directly or indirectly, the composition of the board of directors or board of management, of that party, whether through the ownership of voting securities, by contract or otherwise;

Data Warehouse Repository means a single data warehouse consisting of one or more object sets (e.g. dimensional, normalized or data store) as defined in the License Fee invoice and confirmed by you when using the WhereScape RED License Key, and underlying support tables and utilities on one or more hardware devices sharing common objects (including but not limited to dimension tables) and may include copies or near copies used for development and testing purposes;

Documentation means software user guides (including those in electronic form), handbooks, maintenance libraries, educational materials and all other related material supplied by the Company to the Licensee for aiding the use of the Software;

Initial Support Period means the first 12 months Support Services, commencing on the date of the invoice for the License Fee and ceasing on the same date in the following year;

- Click **ACCEPT** to confirm the type of license.

Note:

If the key fails to validate contact support@wherescape.com.

Checking your Windows Version

WhereScape RED is supported on Windows 8.1 to Windows 10, UNIX or Linux environment with a screen size set to at least 1024x768. This step simply validates that the above requirements have been met.


The WhereScape RED Scheduler is supported on Windows Server 2012 to Windows Server 2019, UNIX or Linux. WhereScape RED will not run under Windows 95, 98 or NT.

Note:


If the minimum screen size of 1024x768 is used, then the standard font size must also be used.

To check your Windows version:

1. In WhereScape's **Setup Administrator**, click the **Computer Setup** tab in the left pane and then click the **Check Windows Version** icon.



Windows Setup details are displayed in the right pane as shown in the following screen:



Checking ODBC Drivers

SQL Server ODBC drivers are shipped in Windows Server, Windows 7, Windows 8 and Windows 10. This step is usually a validation of the pre-installed drivers.


WhereScape RED connects to the data warehouse database using ODBC. This step checks that ODBC drivers are present and up to date.

To check ODBC Drivers:

1. In WhereScape's **Setup Administrator**, click the **Computer Setup** tab in the left pane and then click the **Check ODBC Drivers** icon.



A list of ODBC drivers is displayed, provided the computer user has enough privileges to access the registry:




Creating an ODBC Connection

To create an ODBC Connection:


1. In WhereScape's **Setup Administrator**, click the **Computer Setup** tab and then click **Validate/Add ODBC Source**.



2. An entry needs to exist in the ODBC tables for the data warehouse database. This step lists all entries found that use an ODBC driver. If no entry exists for the data warehouse database, then you need to add one.
 - o Right-click anywhere in the right pane to bring up the **Launch ODBC Data Source Administrator** menu option.



- Click the **System DSN** tab to view the system wide ODBC entries.




- Click the **Add...** button to add a new entry.


Note:

ODBC connections must be either User DSN or System DSN. File DSN connections are not supported.

4. From the **Create a New Data Source** screen, select the relevant driver and then click **Finish**.



The **ODBC Text Setup** dialog is displayed:



5. Enter the relevant details and click the **OK** button to create a new ODBC data source.

SQL Server Installation and Configuration

Introduction

The steps provided here are an indication of the normal process required to install and configure WhereScape RED.

In some environments additional processes will be required.

1. Install the WhereScape RED software onto your PC. Refer to [Installing RED for SQL Server](#) for details.
2. Add your license key. Refer to [Adding your License](#) for details.
3. Check your Windows version. Refer to [Checking your Windows Version](#) for details.
4. Check your ODBC Drivers. Refer to [Checking your ODBC Drivers](#) for details.
5. Designate a database that is to be used as the data warehouse database. Refer to [Creating a SQL Server Database](#) for details.
6. Add the definition of an ODBC data source to connect to the data warehouse database. Refer to [Configuring a SQL Server Metadata Connection \(DSN\)](#) for details.
7. Create the WhereScape metadata repository. Refer to [Creating a Metadata Repository for SQL Server](#) for details.
8. Install a Windows Scheduler. Refer to [Installing a Windows Scheduler for SQL Server](#) for details.
9. If required, load the WhereScape tutorial tables into a separate database. It is highly recommended that the tutorials be undertaken. Refer to [Creating Tutorial Data](#) for details.

Note:

A Quick Start option is available for SQL Server. This option performs all the required tasks (except the entry of a license key) when provided with a valid database server

Problem Solving

If any problems happen in your install that cannot be resolved, proceed as follows when running WhereScape's Setup Administrator utility:

1. Create a log file by selecting **Tools > Start Logging** from the menu bar. Enter a file name.
2. Step through at least:
 - o Computer Setup > Check Windows version.
 - o Computer Setup > Check ODBC drivers.
 - o Computer Setup > Validate/Add ODBC Source.
 - o Metadata Repository > Validate meta repository.
3. Select **Tools > Stop Logging** to close off the log.
4. Edit the log and remove any passwords that appear.
5. Send your log file to support@wherescape.com.

Installing RED for SQL Server

Installation Prerequisites

WhereScape RED requires certain client and server components.

Client Prerequisites

- Windows 8.x and Windows 10
- 4GB RAM minimum
- 2GB available disk space.

- ODBC Version 3.0 (normally shipped as part of the Operating System).
- For building a data warehouse, the appropriate Microsoft ODBC driver for SQL Server is required.

Server Prerequisites

- RED requires SQL Server versions beginning from 2012 to SQL Server 2019.
- To use the WhereScape RED Scheduler, a UNIX, Linux or Windows based server is also required (this may be the database server). WhereScape RED only supports sh and ksh under UNIX and bash under Linux.

Installation of WhereScape RED

To install WhereScape RED, refer to [Installing WhereScape RED](#) for details.

SQL Server Database and Login Setup

SQL Server Database

Create a SQL Server database to be used as the RED metadata repository and data warehouse.

To use object placement across multiple schemas in RED, create the required schemas in the SQL database.

Note

The database name used for the RED repository must follow SQL Server rules for "Regular Identifiers". For example, the database name should not contain any spaces. Please refer to SQL Server documentation for more details on rules for regular identifiers.

SQL Server Login Setup

Create an SQL Server login that will be used to set up the RED metadata repository and for access by the RED scheduler service. The minimum SQL Server permissions are as follows:

Server Level Permissions

- **bulkadmin** - this role is required if you want to load files or use Native ODBC loads.

Permissions to kill a process when killing jobs in the scheduler

- VIEW SERVER STATE
- ALTER ANY CONNECTION

SQL Server 2012 roles

For SQL Server 2012 and later only, users can create server roles and grant them to the RED scheduler and RED users.

Database Permissions

Database roles (on the database with the RED metadata in it)

- db_datareader
- db_datawriter
- db_ddladmin

Database grants (on the database with the RED metadata in it)

- SELECT

- INSERT
- UPDATE
- DELETE
- EXECUTE

Note

When creating a new repository or validating the metadata in an existing repository, the SQL Server login used must have `SYSADMIN` or the `ALTER TRACE` permission.


This is because almost all the WhereScape procedures have a catch all with log file option exception handler. This ensures that if the scheduler cannot log errors to the database, it can log errors to SQL Server logs and Application logs.

The SQL Server login for RED must have a default schema of `dbo`.


Configuring a SQL Server Metadata Connection (DSN)

To begin adding an ODBC Source from **WhereScape's Setup Administrator**, refer to [Creating an ODBC Connection](#) for details.


1. In **ODBC Data Source Administrator**, click the **System DSN** tab to view the system wide ODBC entries.
 - o Click the **Add...** to add a new entry.




2. Select an **SQL Server** driver from the driver list.




3. Enter a **Name** for the ODBC Source and select or enter the **Server**.
 - o Click **Next**.




4. Another pop-up appears with authentication details.
 - o Change as required or leave as shown if you are unsure.
 - o Click **Next**.




5. The next pop-up provides the opportunity to select a database. The following example shows the selection of the Northwind database.
 - o Select a database from the drop-down-list and click **Next**.



6. The last pop-up enables setting of other features if desired.
 - o Ensure the **regional settings** check-box is **not used**. If this is used, then date and number formats will be in regional standards rather than native form.
 - o Click **Finish**.



7. Test the data source using the 'Test Data Source...' button, otherwise just click **OK**.



Tip:

If multiple PCs will access the data warehouse, they must all use the same data source name as entered here.

Creating a Metadata Repository for SQL Server


1. In WhereScape's Setup Administrator, click the **Metadata Repository** tab and then click **Create Metadata Repository**.



2. This option creates the WhereScape meta tables, sequences and procedures in the specified schema. It checks to ensure that the schema, database or user does not contain an existing metadata repository before starting the metadata install.
 - o Click **Create Metadata Repository**.
 - o Enter the **ODBC Connect**, **User Name** and **Password** and then click **OK**.

 A screenshot of a dialog box titled 'Meta Repository Logon'. The dialog has a close button (X) in the top right corner. Below the title bar, there is a message: 'Select the ODBC data source and Log on to the User where the NEW Data Warehouse is to be created.' There are three input fields: 'Data Source:' with a dropdown menu showing 'DocWarehouse', 'User Name:' with a text box containing 'demo', and 'Password:' with a text box containing ten dots. At the bottom right, there are two buttons: 'OK' and 'Cancel'.

3. When creating an SQL Server metadata repository, an additional screen is displayed requesting **Filegroup** information.
 - o Select the required **Filegroups** and then click **OK**.
 - o If Filegroups are not being used, leave the Filegroups fields blank and then click **OK**.



The image shows a dialog box titled "Define FileGroups" with a close button (X) in the top right corner. It contains three rows, each with a label and a dropdown menu:

- Meta repository filegroup: []
- Dimension table filegroup: []
- Dimension index filegroup: []

At the bottom of the dialog are two buttons: "OK" and "Cancel".

Notes:

- The metadata repository and data warehouse tables must both be created under the **dbo** schema when using SQL Server as the data warehouse server.
- Ensure that the user creating the meta repository has the required privileges to create objects in **dbo**.

SQL Server Quick Start


The quick start component of WhereScape's Setup Administrator attempts to do a rapid install of WhereScape RED onto a SQL Server database server.

It creates two databases on this server and then installs the RED software and the tutorial; finally invoking WhereScape RED and the on-line tutorial help.


1. On the **Quick Start** tab, click **Auto install Metadata** to start.



2. The following prompt is displayed.
 - o Click **Yes** to proceed with the creation of the databases.



3. You are first asked for the SQL Server instance in which to load the metadata repository and tutorial. The following window is presented.



RED will attempt to locate all SQL Server servers available and list them in the drop-down. This process can fail for a number of reasons in which case the **Instance** name will need to be ascertained and entered.

Leave the **Username** and **Password** blank, if using a trusted connection and no password is required. Click **OK** when complete.

Once the install has completed, RED will allow you to logon to the newly created data warehouse.


SQL Server Quick Application

The quick application option for SQL Server attempts to create a Data Warehouse database, populate that database with the WhereScape metadata, load an application, install a scheduler and optionally run a batch job. It provides a means of quickly installing a RED application and getting the contents of the tables loaded and populated.

1. On the **Quick Start** tab, click **Auto Install Metadata and Application** to start.



2. The following window is displayed.



- o Click **Yes** to proceed.
3. The following window is displayed.

Choose an Application and Database Name etc

A WhereScape RED data warehouse repository will be created in a new database on the chosen instance of SQL Server. An application will be loaded into this repository and all the objects created.

A scheduler for this repository will be installed on the local machine and a job queued to run. An ODBC source DSN will also be created to be used by the data warehouse source connection.

Select an instance of Sql Server in which to install the new data warehouse.

DocWarehouse

Enter an administrator logon and password to the database, or leave blank for a trusted connection.

Username: Doc

Password: Wsl123

Enter the database name which will become the new data warehouse repository.

newDW

Please enter the location and name of the application id file (app_id_*.wst)

C:\Program Files (x86)\WhereScape\Application\app_id_SQLT_tutorial_1.wst

Browse

Enter the name of a job to queue to run.

Daily Update

An ODBC source (DSN) to be used by the data warehouse source connection will be created.

Enter the ODBC source DSN.

WslTutorial

Select the instance for the database containing the source data.

DocWarehouse

Enter the source database name.

WslTutorial

OK

Trusted connection

Cancel

- o Once all the values have been entered, click **OK** to proceed with the creation of the databases and the loading of the application.

The quick application can also be initiated from the command line or from a Windows batch file.

Windows Command Line Invocation

The syntax for calling from the command line is as follows:

```
adm.exe -QA [-SWITCH "switch value"]
```

The switches that can be applied supply information to the Setup Administrator utility. When all switches are provided, the application install occurs automatically. Where some switches are left out a partially completed, a window appears. The missing information can be provided and the install then proceeds.

Note:

Where a parameter for a switch contains spaces, the parameter must be enclosed in double quotes.

The switches are:

Switch	Parameter to be supplied
-QA	Indicates that this is a "Quick Application". No parameter is required.
-SS	The SQL Server instance name where the Data Warehouse database will reside.
-SL	The administrator user name for the SQL Server instance defined with the -SS switch. If this switch is not provided a Trusted connection is assumed.
-SP	The administrator password for the SQL Server instance defined with the -SS switch.
-SN	The Data Warehouse database name. This database will be created in the instance defined by -SS. An ODBC Source DSN of the same name will also be created on the PC.
-a	The ODBC DSN architecture.
-AN	The RED application name. This is the name of the 'id' file and is typically of the structure app_id_XXXX_vvvvvv.wst where XXXX is the application identifier and vvvvvv is the application version. For example, the tutorial application would be app_id_SQLT_tutorial_6.wst
-AD	The RED application directory. This is the directory in which the file defined by the -AN switch resides.
-LI	The SQL Server instance that contains the source database.
-LD	The ODBC source DSN name as defined in the Connection object in the data warehouse application. This ODBC source will be created.
-LN	The database name on the SQL Server instance as defined by the -LI switch. This is the database that contains the source data.
-LT	This switch does not have a parameter. If set, it flags the ODBC source DSN as defined in the -LD switch as a trusted connection.
-JN	The name of a job in the data warehouse that is to be run once all other tasks are completed.
-CC	The name of the cube connection if appropriate. If set, then all cubes will be updated to have this as the Analysis Services connection.
-DC	The name of the Data Warehouse connection if appropriate. If set, then all cubes will be updated to have this as their Source connection.
-CD	The name of the cube database in Analysis Services if appropriate. If set, then all cubes will be updated to have this database as their Analysis Services database.
-ML	The scheduler login name.
-MP	The scheduler password.

For example, a batch file to call an application load of the tutorial may look as follows:

```
@echo off
c:\
cd \Program Files\WhereScape\
adm -QA -SS "WSL-TEST" -SN new_dw -LT -AN app_id_SQLT_tutorial_3.wst -AD "c:\Program
Files\WhereScape\" -LI WSL-TEST -LD tutorial -LN tutorial -JN "Daily Update" -CC Cubes -CD
My_database -DC DataWarehouse
exit
```

Teradata Installation and Configuration

Introduction

The steps provided here are an indication of the normal process required to install and configure WhereScape RED. In some environments additional processes will be required.

1. Install Teradata Tools and Utilities 13.10 (or greater) or on a suitable computer. These tools and utility components are required:
 - o CLI
 - o Teradata ODBC Driver
 - o BTEQ
 - o Fast Load / Multiload or TPT
 - o Fast Export
2. Install the WhereScape RED software onto your PC. Refer to [Installing RED for Teradata](#) for details.
3. Add your license key. Refer to [Adding your License](#) for details.
4. Check your Windows version. Refer to [Checking your Windows Version](#) for details.
5. Check your ODBC Drivers. Refer to [Checking your ODBC Drivers](#) for details.
6. Designate a database or user that is to be used as the meta data database. For testing or evaluation purposes this database or user may be a Teradata Express database server. WhereScape RED requires the Teradata database version 15.10 or greater as the data warehouse database server. Record the database and server names for this database. Create a database user to hold the metadata tables.
7. Allocate the privileges required by WhereScape RED. Refer to [Creating a Teradata Environment](#) for details.
8. Add appropriate entries to the hosts file on the computer for the server.
9. Add a definition of an ODBC data source to connect to the data warehouse database. Refer to [Configuring a Teradata Metadata Connection \(DSN\)](#) for details.
10. Create the WhereScape metadata repository under the data warehouse user that you created. Refer to [Creating a Metadata Repository for Teradata](#) for details.
11. Install a Windows Scheduler. Refer to [Installing a Windows Scheduler for Teradata](#) for details.
12. Install a Unix Scheduler. Refer to [Installing a Unix Scheduler for Teradata](#) for details.
13. Install a Teradata Unix Loader. Refer to [Installing a Teradata Unix Loader](#) for details.
14. If required, load the WhereScape tutorial tables into a separate database. It is highly recommended that the tutorials be undertaken. Refer to [Creating Tutorial Data](#) for details.

Problem Solving

If problems occur in your install that cannot be resolved, proceed as follows when running WhereScape's Setup Administrator utility:

1. Create a log file by selecting **Tools > Start Logging** from the menu bar. Enter a file name.

2. Step through at least:
 - o Computer Setup > Check Windows version.
 - o Computer Setup > Check ODBC driver.
 - o Computer Setup > Validate/Add Odbc source.
 - o Create/Validate Meta Repository > Validate meta repository.
3. Select **Tools > Stop Logging** to close off the log.
4. Edit the log and remove any passwords that appear.
5. Send your log file to support@wherescape.com.

Installing RED for Teradata

Installation Prerequisites

WhereScape RED requires certain client and server components.

Client Prerequisites

- Windows 8.x and Windows 10.
- 2GB available disk space.
- ODBC Version 3.0 (normally shipped as part of the Operating System).
- For building a data warehouse, Teradata Tools and Utilities 15.10 or greater is required.

Server Prerequisites

- One of the following data warehouse database platforms is required: 15.10, 16.00, 16.10, 16.20.
- To use the WhereScape RED Scheduler, a UNIX, Linux or Windows based server is also required (this may be the database server). WhereScape RED only supports sh and ksh under UNIX and bash under Linux.
- When installing a Unix/Linux scheduler, the server will need to have Teradata Tools and Utilities for Linux/UNIX installed and configured as a prerequisite before the scheduler can be installed.

Installation of WhereScape RED

To install WhereScape RED, refer to [Installing WhereScape RED](#) for details.

Creating a Teradata Environment

The creation of the Teradata repository and user(s) that are used to administer and maintain the data warehouse must be performed outside of this utility.

The RED repository is recommended to be a Teradata database for a more secure database environment.

WhereScape recommends following Teradata best practices related to ROLES and PROFILES but does not mandate they be used.

RED repositories require these permissions for administration:

```
GRANT EXECUTE, SELECT, INSERT, UPDATE, DELETE, STATISTICS, SHOW, TABLE, VIEW, MACRO ON
RED_REPOSITORY TO RED_REPOSITORY;
GRANT EXECUTE PROCEDURE ON RED_REPOSITORY TO RED_REPOSITORY WITH GRANT OPTION;
```

RED developers do not need TABLE or VIEW permissions to the repository database.

RED developers only require INSERT, UPDATE, DELETE and SELECT on metadata repository views. Please contact WhereScape should you need assistance in configuring a Teradata secure repository environment.

For DBC permissions the following is required:

GRANT SELECT ON DBC.ErrorMsgs; – to log error messages into error logs. This is always accessed through the locking for access modifier.

GRANT SELECT ON DBC.TablesV; – to describe Tables in a database within databases the user has permission to.

GRANT SELECT ON DBC.ColumnsV; – to describe columns associated with a table within databases the user has permission to.

Note: COLLATION

If your Teradata database's default collation is UNICODE, please ensure that the user must be created with COLLATION = ASCII, DEFAULT CHARACTER SET LATIN;

As an example, for our data warehouse, or decision support system, we will create a user, 'dssdemo'. An example SQL script to create this 'dssdemo' user is shipped and can be found in the WhereScape RED program directory:

- ..\Teradata\Recreate_dssdemo.sql

This script needs to be **modified** to reflect the Teradata environment created at your site.

Note: Timezone Settings

Teradata can generate CURRENT_TIMESTAMP, CURRENT_TIME and CURRENT_DATE to reflect the session time and session time zone (as opposed to the current date and time on the Teradata server).

This can result in date/time/timestamp comparisons behaving unexpectedly and impact the RED scheduler. A Teradata Customer Service Engineer can configure this using a DBSCONTROL field called TimeDateWZControl.

The values for TimeDateWZControl are:


- 1 (disabled)
- 2 (enabled with UTC i.e. all datetime data is stored in UTC on disk)
- 3 (enabled with LOCAL i.e. all datetime data is stored in system LOCAL time on disk)
- 0 (returns the field to disabled)

Please ensure **TimeDateWZControl** is disabled, if you are not using temporal fields.

Configuring a Teradata Metadata Connection (DSN)

To begin adding an ODBC Source from WhereScape's Setup Administrator, refer to [Creating an ODBC Connection](#) for details.

1. In **ODBC Data Source Administrator**, click on the **System DSN** tab to view the system wide ODBC entries.
 - o Click on the 'Add...' button to add a new entry.
2. Select a **Teradata** driver from the driver list.



3. A pop-up as shown below appears.
 - o Enter a **Name** for the Data Source.
 - o Next, enter the **Name or IP Address** for the Teradata Server Info.
 - o The **Session Character Set** field must be set to **ASCII** - this is the only character-encoding scheme supported for Teradata.

Note

The name entered for the **Teradata Server Name** should appear in the **hosts** file on the computer in this form:


(IP address) (Teradata Server Name) (Teradata Server Name)Cop1

For the example in the ODBC screen shot above for TD_14_00, this entry would present if the server had an IP address of 10.12.123.60 and a name of "TD_14_00":

10.12.123.60 TD_14_00 TD_14_00Cop1

An alternative approach is to add the same entry to a dynamic name server (DNS).

4. If using the ODBC source for a RED Scheduler, click **Run in Quiet Mode**.
 - o Click **OK**.



5. Click **OK** again.


Tip

If multiple PCs will access the data warehouse, they must all use the same data source name as entered here.

Creating a Metadata Repository for Teradata

1. In **WhereScape's Setup Administrator**, click on the **Metadata Repository** tab in the left pane and then click on the **Create Metadata Repository** icon.

This option will create the WhereScape meta tables, sequences and procedures in the specified schema. It checks to ensure that the schema, database or user does not contain an existing metadata repository before starting the metadata install.




2. After clicking on **Create Metadata Repository**, enter the **ODBC Connect**, **User Name** and **Password** or **TD Wallet String**.
 - o Click **OK**.

 A dialog box titled 'Meta Repository Logon' with a red close button in the top right corner. The text inside reads: 'Select the ODBC data source and Log on to the User where the NEW Data Warehouse is to be created.' Below this are three rows of input fields:

- 'Odbc Connect' with a dropdown menu showing 'Teradata'.
- 'User Name' with a text box containing 'dssdemo'.
- 'Password' with a text box containing 'You TD Wallet String or Password'.

 To the right of the 'User Name' and 'Password' fields are 'OK' and 'Cancel' buttons respectively. At the bottom, there is a checked checkbox labeled 'Password is TDWallet string.'

3. When creating a Teradata metadata repository, two additional screens are displayed:
 - o First, a dialog is displayed for the Teradata server name (TDPID). Enter the **TDPID**.
 - o Click **Test and Use**. If you skip the test and provide an invalid or wrong **Teradata TDPID**, native loads will not work in WhereScape RED.



Meta Repository Logon

Select the ODBC data source and Log on to the User where the NEW Data Warehouse is to be created.

Data Source: DocWarehouse

User Name: demo

Password: [masked]

OK Cancel

Note

The name entered for the **Teradata Server Name** should appear in the **hosts** file on the computer in this form:


(IP address) (Teradata Server Name) (Teradata Server Name)Cop1

For the example in the ODBC screen shot above for TD_14_00, this entry would present if the server had an IP address of 10.12.123.60 and a name of "TD_14_00":

10.12.123.60 TD_14_00 TD_14_00Cop1

An alternative approach is to add the same entry to a dynamic name server (DNS).

4. A second additional dialog is displayed for the Metadata Repository database.
 - o Enter the name of the user or database in which the metadata repository is being created.
 - o Click **OK**.



Define FileGroups

Meta repository filegroup: []

Dimension table filegroup: []

Dimension index filegroup: []

OK Cancel

Oracle Installation and Configuration

Introduction

The steps provided here are an indication of the normal process required to install and configure WhereScape RED. In some environments, additional processes will be required.

1. Install the Oracle 10g, 11g or higher database client software on a suitable PC.
2. Install the WhereScape RED software onto your PC. Refer to [Installing RED for Oracle](#) for details.
3. Add your license key. Refer to [Adding your License](#) for details.
4. Check your Windows version. Refer to [Checking your Windows Version](#) for details.
5. Check your ODBC Drivers. Refer to [Checking your ODBC Drivers](#) for details.
6. Designate a database that is to be used as the data warehouse database. For testing or evaluation purposes this may be a PC based database. WhereScape RED requires the Oracle database version 10.1 or greater as the data warehouse database. Record the SID for this database. Create the database user (schema) that is to be used to hold the metadata and data warehouse tables. Allocate the privileges required by WhereScape RED. Refer to [Creating an Oracle DSS User](#) for details.
7. Establish the Oracle Net connections required to allow access to the data warehouse database from the PC. Record the **Server** name for the connection.
8. Add the definition of an ODBC data source to connect to the data warehouse database. Refer to [Configuring an Oracle Metadata Connection \(DSN\)](#) for details.
9. Create the WhereScape metadata repository under the data warehouse schema that you created. Refer to [Creating a Metadata Repository for Oracle](#) for details.
10. Install a Windows Scheduler. Refer to [Installing a Windows Scheduler for Oracle](#) for details.
11. Install a Unix Scheduler. Refer to [Installing a Unix Scheduler for Oracle](#) for details.
12. If required, load the WhereScape tutorial tables into a separate database. It is highly recommended that the tutorials be undertaken. Refer to [Creating Tutorial Data](#) for details.

Problem Solving

If problems occur in your install that cannot be resolved proceed as follows when running WhereScape's Setup Administrator utility:

1. Create a log file by selecting **Tools > Start Logging** from the menu bar. Enter a file name.
2. Step through at least:
 - o Computer Setup > Check Windows version.
 - o Computer Setup > Check ODBC drivers.
 - o Computer Setup > Validate/Add Odbc source.
 - o Oracle> Validate Oracle user privileges (if an Oracle DataWarehouse).
 - o Create/Validate Meta Repository > Validate meta repository.
3. Select **Tools > Stop Logging** to close off the log
4. Edit the log and remove any passwords that appear.

5. Send your log file to support@wherescape.com.

Installing RED for Oracle

Installation Prerequisites

WhereScape RED requires certain client and server components.

Client Prerequisites

- Windows 8.x and Windows 10
- 2GB available disk space.
- ODBC Version 3.0 (normally shipped as part of the Operating System).
- For building a data warehouse, a version 11.2 database client or greater is required. A 32-bit or 64-bit Oracle client installation will be necessary (64-bit recommended).

Server Prerequisites

- One of the following data warehouse database platforms is required: Oracle version 11.2 or higher.
- To use the WhereScape RED Scheduler, a UNIX, Linux or Windows based server is also required (this may be the database server). WhereScape RED only supports sh and ksh under UNIX and bash under Linux.

Installation of WhereScape RED

To install WhereScape RED, refer to [Installing WhereScape RED](#) for details.

Notes:

The WhereScape RED installer selects the following installation directory as the default location for RED on a 64-bit windows server: C:\Program Files (x86)\WhereScape. This is where 32-bit applications normally reside on a 64-bit Windows platform.

However, if Oracle 10g is involved, either as the data warehouse repository, or as a source system, installing RED in "Program Files (x86)" can cause an issue. Oracle does not like directories that have a parenthesis in their name. Applications using Oracle cannot be located in such a directory. This includes WhereScape RED using ODBC to connect to Oracle. The result is that WhereScape RED will not be able to connect to Oracle. (This issue does not usually occur with Oracle 11g). To prevent this, change the installation directory of WhereScape RED. Options include:

C:\WhereScape
D:\Program Files\WhereScape (if a second drive is available)

It is not good practice to install 32-bit applications in C:\Program Files\WhereScape on a 64-bit machine.

Creating an Oracle User

The creation of the Oracle database user that will be used to administer and maintain the data warehouse must be performed outside this utility. The **SQL Admin** utility can be used to execute the sql required to create such a user, or the database administrator should be contacted.

A list of the required privileges is displayed when this option is selected. Many of these privileges must be allocated as specific privileges and cannot be granted as part of a role. For example, if a 'grant dba to dssuser' command is executed WhereScape RED will still need these privileges specifically granted as 'dba' is a roll.

Note

WhereScape RED makes use of the `dbms_lock` and `dbms_sql` packages supplied by Oracle. When using Oracle, privileges obtained by the owner via a role cannot be referenced in a procedure. Therefore, RED requires that these privileges be granted to the user. This is an Oracle restriction and not something imposed by WhereScape.

For our data warehouse, or decision support system, we will create a user, 'dssdemo'. An example sql script to create this 'dssdemo' user is shipped and can be found in the WhereScape RED program directory:

- `..\Oracle\Recreate_dssdemo.sql`

Notes

- This script need to be **modified** to reflect the data warehouse schema chosen at your site. An example script follows below.
- This script would normally need to be run under the sys user.

1. The dss user created is dssdemo in this case:

```
drop user dssdemo cascade;
create user dssdemo identified by wsl;
alter user dssdemo default tablespace DEMODATA;
alter user dssdemo temporary tablespace TEMP;

grant create session to dssdemo;
grant resource to dssdemo;
grant create table to dssdemo;
grant create view to dssdemo;
grant create sequence to dssdemo;
grant create procedure to dssdemo;
grant select any table to dssdemo;
grant create materialized view to dssdemo;
grant create database link to dssdemo;
grant query rewrite to dssdemo;
grant select on sys.v_$database to dssdemo;
grant alter session to dssdemo;
grant select on sys.v_$session to dssdemo;
grant execute on sys.dbms_lock to dssdemo;
grant execute on sys.dbms_sql to dssdemo;
grant create any view to dssdemo;
grant unlimited tablespace to dssdemo;
grant alter system to dssdemo;
grant select_catalog_role to dssdemo;
```

Notes

- **select any table** - this is only required to gain access to tables in other schema. It is not required if specific grants have been provided to the tables that are required, such as with the tutorial.
- **alter system** - some dbas do not like granting the ALTER SYSTEM privilege as it is very powerful. With this privilege, you can make wide reaching changes including altering initialization parameters. RED only uses ALTER SYSTEM to kill jobs. Rather than granting ALTER SYSTEM, you can compile `Ws_User_Abort` (contained in `C:\Program Files\WhereScape\Oracle`) under the SYS user. Then grant `execute on SYS.Ws_User_Abort to dssdemo`.

2. To use object placement **across multiple schemas** in WhereScape RED, the RED user also needs to be granted the following privileges:

```
grant select any table to dssdemo;
grant create any view to dssdemo;
grant drop any view to dssdemo;
grant create any table to dssdemo;
grant drop any table to dssdemo;
grant delete any table to dssdemo;
grant insert any table to dssdemo;
grant update any table to dssdemo;
grant alter any table to dssdemo;
grant global query rewrite to dssdemo;
grant create any materialized view to dssdemo;
grant drop any materialized view to dssdemo;
grant alter any materialized view to dssdemo;
grant create any index to dssdemo;
grant drop any index to dssdemo;
grant alter any index to dssdemo;
grant select any sequence to dssdemo;
grant create any sequence to dssdemo;
grant drop any sequence to dssdemo;
grant analyze any to dssdemo;
grant comment any table to dssdemo;

grant select_catalog_role to dssdemo;
```

3. To do loads from **Hadoop** using multiple schemas, the RED user also needs to be granted the following privilege:

```
grant select_catalog_role to dssdemo;
```

4. To use the Data Vault 2 templates, the RED user also needs to be granted the following privilege:

```
grant execute on dbms_crypto to dssdemo;
```

Creating Oracle Individual Users

Oracle users that require each developer to log into Oracle (using their own username and password), can use the **Oracle Individual User Logon Method**.

The Oracle Individual User option allows a user, with the appropriate permissions, to log into WhereScape RED and then operate as the RED schema.

This method enables customers to configure RED ensuring that users logged in via this method cannot edit the metadata user password in the connections, and ensures that the password is encrypted in **Tools > Options**.

To authorize users to log in to RED using the Oracle Individual User method, a DBA needs to grant users select on the **ws_dbc_connect** table, as well as the **CREATE SESSION** system privilege.

This method is also useful for tracking individual WhereScape RED user activity in the Oracle database. Their authenticating user name is now stored in the CLIENT_IDENTIFIER field of v\$session which can be used by Oracle's auditing, functioning to track individual developer activity.

Oracle individual users will need to be created and granted certain privileges. Alternatively, for existing Oracle database users, they just need to be granted the following privileges below:


```
grant create session to oracle_user1
grant select on dssdemo.ws_dbc_connect to oracle_user1
```

1. Once logged in to RED, the metadata user needs to do the following in **Tools > Options > Repository Privacy settings**:
 - o Check the option to enable the **Mask Extract User Password**.

- o Deselect the option to deactivate the **Extract User Password Editing** (this will lock down the metadata user password in the connections).
- o Check the option to enable the **Mask Admin User Password**.
- o Deselect the option to deactivate the **Enable Admin User Password Editing** (this will lock down the Admin/Dss User Password in the connection properties).


Note: Encrypt User/Admin User Password Options

Users should also check the options to enable **Encrypt User Password** and **Encrypt Admin User password** as shown in the example screen below.



For **UNIX/Linux scheduler** processing User and Password Encryption implications, please refer to section *Settings - Repository Privacy Settings* in the *RED User Guide*.

2. Multiple users can then log in to RED using their own credentials by:
 - o Selecting the **Oracle Individual User** option from the **Logon Method** drop-down menu.
 - o Entering their user name and password.
 - o Entering the RED schema.



WhereScape® RED

Version 8.6.1.0 by WhereScape, Inc.
Copyright © 2020
Licensed to IDERA
For WhereScape employee use only

REPOSITORY LOGIN

DATABASE

Data Source: WslWarehouse ORA

Logon Method: Oracle Individual User

Database Login ID: oracle_user1

Password: *****


METADATA REPOSITORY

RED Schema: dssdemo

RED User Name: WhereScape Documentation

CONNECT CANCEL HELP

3. The **Repository Privacy Settings** is completely unavailable for users that log in to RED via the **Oracle Individual User** method.



Options

- Repository Identification
- Repository Privacy Settings**
- Object Types
- Global Naming Conventions
- DSS Tables and Columns
- Check-Out and Check-In
- Code Generation
- Scheduler
- Storage
- Metadata Versioning
- Documentation
- Data Vault
- Available Load Types
- Other

Update of Meta Admin Table Disabled

Setting	Value
Meta Login Method	Any
Include User Details in Application Deployments	<input checked="" type="checkbox"/>
Extract User ID Settings	
Mask Extract User ID	<input type="checkbox"/>
Enable Extract User ID Editing	<input checked="" type="checkbox"/>
Encrypt Extract User ID	<input type="checkbox"/>
Extract User Password Settings	
Mask Extract User Password	<input checked="" type="checkbox"/>
Enable Extract User Password Editing	<input type="checkbox"/>
Encrypt Extract User Password	<input checked="" type="checkbox"/>
Admin User ID Settings	
Mask Admin User ID	<input type="checkbox"/>
Enable Admin User ID Editing	<input checked="" type="checkbox"/>
Encrypt Admin User ID	<input type="checkbox"/>
Admin User Password Settings	
Mask Admin User Password	<input checked="" type="checkbox"/>
Enable Admin User Password Editing	<input type="checkbox"/>
Encrypt User Admin Password	<input checked="" type="checkbox"/>
Teradata Wallet User ID Settings	
Mask Teradata Wallet User ID	<input type="checkbox"/>
Enable Teradata Wallet User ID Editing	<input checked="" type="checkbox"/>
Encrypt Teradata Wallet User ID	<input type="checkbox"/>
Teradata Wallet String Settings	
Mask Teradata Wallet String	<input type="checkbox"/>
Enable Teradata Wallet String Editing	<input checked="" type="checkbox"/>
Encrypt Teradata Wallet String	<input type="checkbox"/>

Prev Next OK Cancel Help


Tip: Oracle Individual User System Information

The permissions below are required to list and see user session, session locks and user locks information for Oracle individual users.

```
grant select on sys.v_$sql to dssdemo;
```


Tip: Oracle Individual User System Information

```
grant select on sys.v_$sess_io to dssdemo;
grant select on sys.v_$locked_object to dssdemo;
grant select on sys.v_$lock to dssdemo;
```




Configuring an Oracle Metadata Connection (DSN)


WhereScape RED supports the **Oracle** ODBC driver, follow the instructions below for setting up this driver. To begin adding an ODBC Source from WhereScape's Setup Administrator, refer to [Creating an ODBC Connection](#) for details.

Setting up an Oracle ODBC Driver


1. In **ODBC Data Source Administrator**, click the **System DSN** tab to view the system wide ODBC entries.
 - o Click the 'Add...' button to add a new entry.



2. Select the **Oracle ODBC** driver from the driver list.
 - o Click **Finish**.



3. Enter the **ODBC Data Source Name (DSN)** details in the **Oracle ODBC Driver Configuration** screen.



Oracle ODBC Driver Configuration

Data Source Name: dssdemo

Description: dssdemo

TNS Service Name: ORCL11

User ID: 011_Doc_User

Buttons: OK, Cancel, Help, Test Connection

Application: Oracle | Workarounds | SQLServer Migration

Enable Result Sets Enable Query Timeout Read-Only Connection

Enable Closing Cursors Enable Thread Safety

Batch Autocommit Mode: Commit only if all statements succeed

Numeric Settings: Use Oracle NLS settings

- To test the connection, click **Test Connect**, otherwise click **OK**.


Validating Oracle User Privileges

- To validate the Oracle user privileges, click the **Oracle** tab and then click **Validate Oracle User Privileges**.



This option tests that an ODBC connection can be made to the Oracle database running the data warehouse.

The diagram below shows some of the layers involved in making up this type of connection.



If this connection fails, then we need to isolate where the failure is occurring. The Oracle documentation can aid in resolving the problem. Starting from the bottom and working back up the layers we can perform the following tests:

1. Log on to the host running the database, and check that a direct connection to the database works via a tool, such as sqlplus. This will test that the database is active and receiving connections.
2. Issue a Tnsping from a dos shell on the PC (e.g. tnsping ORCL) where ORCL is the tnsnames connection entry for the data warehouse database. This will check the Oracle network layer. If the Tnsping responds with an **OK**, then the database server is visible through the network layer.
3. Connect to the data warehouse database using sqlplus from the PC. Again, this test checks the network layer and a small part of the Oracle client software.
4. Attempt an ODBC connection using the Oracle supplied ODBC tool (normally called **Oracle ODBC Test** and located within the Oracle program menu). This tool is normally loaded as part of the Oracle client. It provides an independent test of the ODBC, Oracle client and network layers. Initially attempt to connect using the Oracle supplied ODBC driver. This will confirm that all layers apart from the ODBC driver are working correctly. If a failure occurs consult the Oracle documentation.
5. Perform the same test as step (4) but this time using the Microsoft® ODBC for Oracle driver.

Notes:

A connect error **NA000** usually means the ODBC driver is not functioning correctly. This may be due to a Microsoft® service pack dependency. Acquire the ODBC drivers from Microsoft® and try again. The file is mdac_typ.exe and is a free download from Microsoft®.

Some combinations of the Oracle client software and the Microsoft® ODBC driver for Oracle result in a connection error **NA000**. If the connection fails and all other possibilities have been checked then the following may address the problem on Windows 2000 systems.


Run RegEdit

Under the HKEY_LOCAL_MACHINE\ SOFTWARE\ Microsoft\ MSDTC\ MTxOCI entry edit OracleOciLib and set it to Oci.dll (The default is Ociw32.dll).

Another common problem is where multiple Oracle homes are in use (especially where Oracle Discoverer has been installed). Ensure that the PATH variable references an 8.1.7 or later Oracle directory. The OCI used by the Microsoft® odbc driver utilizes features not found in older versions of the OCI.

If you are still unable to connect, record the error message as displayed on connection failure and contact support@wherescape.com.

The following example shows the error message "2800 (Microsoft®)(ODBC driver for Oracle)ORA_01017: invalid username/password; logon denied".



Creating a Metadata Repository for Oracle

1. In **WhereScape's Setup Administrator**, click the **Metadata Repository** tab and then click **Create Metadata Repository**.




2. This option creates the WhereScape meta tables, sequences and procedures in the specified schema. It checks to ensure that the schema, database or user does not contain an existing metadata repository before starting the metadata install.
 - o Click **Create Metadata Repository**.
 - o Enter the **ODBC Connect**, **User Name** and **Password** and then click **OK**.

 A screenshot of a dialog box titled 'Meta Repository Logon'. The dialog has a close button (X) in the top right corner. The main text reads: 'Select the ODBC data source and Log on to the User where the NEW Data Warehouse is to be created.' Below this text are three input fields:


- 'Data Source:' with a dropdown menu showing 'DocWarehouse'.
- 'User Name:' with a text box containing 'demo'.
- 'Password:' with a text box containing a series of dots.

 At the bottom right of the dialog are two buttons: 'OK' and 'Cancel'.

3. When creating an Oracle metadata repository, an additional window is displayed requesting **Tablespace** information.
 - o Select the required Tablespaces and then click **OK**.
 - o If Tablespaces are not specified, the user's default Tablespace will be used.




4. Depending on the type of license you have, the following dialog may be displayed:
 - o If it is displayed, select the type of repository required and then click **OK**.



Note:

- o **Repository Types:** This is just setting the default objects visible in RED. They can later be changed in RED under **Tools > Options**.
- o **Data Vault Repository Type:** Depending on the license type, users may have different repository type choices available. Choosing a **Data Vault** repository type will create a metadata repository in RED with more appropriate Data Vault repository default settings, such as Object Type Names, Global Naming of Tables, Indexes, Key Columns and Procedures/Scripts, as well as other repository settings/user preferences.

5. The procedure compile dialog is displayed:
 - o To force the compilation under the Oracle 8i standard, select the check-box on the right bottom corner of the **Procedure Compile** window. Otherwise, click **OK**.



6. If a procedure fails to compile, then scroll to the right in the right pane to see if any of the returned error codes help in ascertaining what the problem is.

For **Oracle** common causes of procedure compilation failures are:

- o Running an Oracle version prior to 11.2.
- o Insufficient room in the SYSTEM table space.
- o Insufficient privileges. (See notes below).
- o Memory parameters set too small in the Oracle instance.

Insufficient privileges on procedure compile (Oracle)

Compiles of the WhereScape procedures may fail where the required privileges have not been granted. The bulk of the WhereScape procedures are used by the scheduler, so they can be left uncompiled, if the scheduler is not to be used. The following procedures however must successfully compile for WhereScape RED to function correctly:

Ws_Procedure_Save, Ws_Procedure_Compile, WsWrkAudit, WsWrkError, WsParameterRead and WsParameterWrite


If one or more procedures fail to compile then use the **Validate Metadata Repository** option to compile the procedures, once the problem has been rectified.

Tutorial Data

The tutorial data component of **WhereScape's Setup Administrator** attempts to validate, upgrade or perform an initial install of the WhereScape tutorial tables.

The tutorial tables are only required if the tutorial is to be undertaken. They can be ignored if desired.

1. Click the **Metadata Repository** tab in the left pane and then click either:
 - o The [Create Tutorial Data](#) option to create (or re-create) the set of tables in the specified schema (user).
 - o The [Validate Tutorial Data](#) option to check for the existence of WhereScape RED tutorial tables.



Creating Tutorial Data

1. In WhereScape's Setup Administrator, click the **Metadata Repository** tab and then click **Create Tutorial Data**.



This option creates or re-creates the WhereScape tutorial tables within the schema (user) or database provided. The normal practice is to locate these tables in a different schema from the data warehouse user for Oracle and in a different database for SQL Server. The data warehouse user will need select access to these tables to perform the tutorial. The tutorial documentation assumes these tutorial tables will be loaded under the user 'wtutorial' for Oracle or in the Tutorial database for SQL Server. Another user or database may be used if desired. The user chosen must have sufficient privileges to allow the creation of the tables.

When this option is selected, an ODBC connection dialog appears and if a valid user is entered the tables will be created and populated under the specified user.

Please ensure that no tables that match those shown in the Validate tutorial tables section exist under the specified user. If existing tables are found, a prompt is issued, and if proceed is chosen then all data will be deleted from the tables and the tutorial data loaded.

Teradata

When creating tutorial tables for Teradata, an additional dialog is displayed for the user or database name that the tutorial data will be created.

- Enter the name of the user or database in which the tutorial data will be created and click **OK**.

Validating Tutorial Data

1. In **WhereScape's Setup Administrator**, click the **Metadata Repository** tab and then click **Validate Tutorial Data**.



The tables are based around a simple sales model and are as follows:


This option validates that the tutorial tables exist in the given schema.

Table	Contents
product	A list of products including a product code (sku), description, group and subgroup.
prod_group	A description of each product group.
prod_subgroup	A description of each product sub group.
prod_line	A description of each product line.
code_table	A table containing the codes and descriptions for product groups, sub groups and lines. A code type of 'pg','sg' and 'pl' is used to differentiate the different codes.
customer	A list of customers containing names and addresses.
order_line	The lines on a sale. Includes the specific product code, quantities and values.
order_header	The header for a sale. Includes the customer code, order data and ship date.
kpi	Used to generate a KPI dimension.
budget	Budget data for sales of products to customers.
forecast	Demand forecast data for products and customers.

Applications


The application component of WhereScape's Setup Administrator attempts to list, upgrade or perform an initial install of a third-party supplied data warehouse application.

1. Click the **Application** tab in the left pane and then click:
 - o **Application Load** - Refer to [Loading an Application](#) to load the metadata, tables procedures, scripts etc. provided as part of the application.
 - o **Change Application Directory** - Refer to [Changing the Application Directory](#) to change the directory of applications to be installed.
 - o **List applications in Repository** - Refer to [Listing Applications](#) to list all applications that have been applied to the chosen metadata repository.



Loading an Application

1. In **WhereScape's Setup Administrator**, click the **Application** tab and then click **Application Load**.



Loading an application inserts various objects into the chosen metadata repository. An application is best defined as a set of objects that are shipped to allow inclusion of those objects into a remote repository.

Note:

An application can only be loaded into a metadata repository running on the same database type as the application creator. (e.g. An Oracle application cannot be loaded into a SQL Server metadata repository).

During the load of an application a number of cross environment mappings need to be resolved. These are:

Connections

Connections are normally unique for each metadata repository. They provide the path to the source data and this nearly always varies. Even though an application can ship a set of connections, these connections will nearly always need modification. Alternatively, a connection shipped with an application may map to an existing connection, and this can be done as part of the load process. If you are unsure whether or not a connection is required, it can be added and later modified.

Tablespaces (Filegroups in SQL Server and Databases in Teradata)

If an application ships table or index objects, then these objects will typically have a tablespace (filegroup in SQL Server and database in Teradata) associated with them. During the load, it is necessary to map these tablespaces (filegroups in SQL Server and databases in Teradata) to those available for the metadata repository.

Object Changes

The application may ship objects that already exist in the metadata. In such a case, the process during the load is to create a version of the existing object and then replace it with the new object. At the start of the load, a check is made to see if any objects will be replaced. If the application is a patch or an upgrade of an existing application version, then this will be normal. The load can be stopped at this point to allow for further investigation.

Table Changes

If the load replaces table objects, it may in turn need to alter the physical table in the database to match the new definition. Again, if this is a patch or an application upgrade, this may be desirable. If not, the proposed actions should be reviewed before proceeding.

Procedure Changes

New procedures, scripts, or modifications may be loaded as part of the application load. In the case of procedures, the procedures need to be recompiled. The load can perform this action, but any failures or issues needs to be resolved after the load has been completed.

The following section covers the actual application load process.

Notes:

- It is always a good idea to backup the WhereScape RED metadata before running an application load. Refer to **Backing Up the Metadata before Loading Applications** for details.
- Some database operations, such as converting existing non-partitioned tables to partitioned tables, cannot be done using a deployment application. In such cases, some manual intervention may be required to update the target databases to match the new metadata.

Backing Up the Metadata before Loading Applications

It is always a good idea to backup the WhereScape RED metadata before running an application load.

A metadata backup can be used to restore the metadata to the state before the application was loaded.

There are three options for backing up the metadata:

1. In RED, use the **Backup > Unload the metadata to disk** option to unload the metadata to a WhereScape Proprietary backup. Refer to **Unloading Metadata** in the *WhereScape RED User Guide* for more information.
2. In RED, use the **Backup > Export the metadata** option to backup the metadata, using the data warehouse database's backup utility. Refer to **Backup using DB Routines** in the *WhereScape RED User Guide* for more information.
3. In RED, use the **Tools > Build application tables** option to build an application of the objects being replaced. This is achieved by selecting the new application files you're about to load in the **Previous application** box of the Define and build an application distribution window. Refer to **Application Creation** in the *WhereScape RED User Guide* for more information.

Note:

If the table changes in the application are being applied to the data warehouse database, then it is also a good idea to backup the data warehouse tables being changed.

Application Load Process

An application consists of multiple files that are loaded from a directory. The default directory is the WhereScape program directory. Another directory may be specified by clicking the **Change Application Directory** button. The last selected application directory is the default directory for the next application load.

Once the directory has been selected, the application load is started by clicking the **Application Load** button. This displays the available applications in the right pane.

Note:

If the **Change Application Directory** button was used, the list of available applications will already be displayed and the **Application Load** button doesn't need to be clicked.

An example application list follows:

Available Applications					
App Id	Version	Metadata Version	Database	File Name	Comments
SQLT	base_1	6.8	SQL Server	app_id_SQLT_base_1.wst	Base 1- dim_date
SQLT	templates	6.8	SQL Server	app_id_SQLT_templates.wst	This application contains all templates use...
SQLT	tutorial_1	6.8	SQL Server	app_id_SQLT_tutorial_1.wst	Tutorial 1 - Basic star schema fact table
SQLT	tutorial_2	6.8	SQL Server	app_id_SQLT_tutorial_2.wst	Tutorial 2 - Rollup fact tables, ASCII file loa...
SQLT	tutorial_3	6.8	SQL Server	app_id_SQLT_tutorial_3.wst	Tutorial 3 - Scheduling and dependencies ;
SQLT	tutorial_4	6.8	SQL Server	app_id_SQLT_tutorial_4.wst	Tutorial 4 - Complex dimensions and hiera...
SQLT	tutorial_5	6.8	SQL Server	app_id_SQLT_tutorial_5.wst	Tutorial 5 - Analysis Services Cubes
SQLT	tutorial_6	6.8	SQL Server	app_id_SQLT_tutorial_6.wst	Tutorial 6 - KPI fact tables
TERT	tutorial_1	6.8	Teradata	app_id_TERT_tutorial_1.wst	Tutorial 1 - Populating a Defined Model
WSLT	base_1	6.8	Oracle	app_id_WSLT_base_1.wst	Base 1 - dim_date
WSLT	templates	6.8	Oracle	app_id_WSLT_templates.wst	This application contains all templates use...
WSLT	tutorial_1	6.8	Oracle	app_id_WSLT_tutorial_1.wst	Tutorial 1 - Basic Star Schema Fact Table
WSLT	tutorial_2	6.8	Oracle	app_id_WSLT_tutorial_2.wst	Tutorial 2 - Rollup fact tables, ASCII file loa...
WSLT	tutorial_3	6.8	Oracle	app_id_WSLT_tutorial_3.wst	Tutorial 3 - Scheduling and dependencies
WSLT	tutorial_4	6.8	Oracle	app_id_WSLT_tutorial_4.wst	Tutorial 4 - Complex Dimensions and Hiera...
WSLT	tutorial_5	6.8	Oracle	app_id_WSLT_tutorial_5.wst	Tutorial 5 - Analysis Services Cubes
WSLT	tutorial_6	6.8	Oracle	app_id_WSLT_tutorial_6.wst	Tutorial 6 - KPI Fact Tables

- To load an application, either right-click the Application from the list and select **Install Application** from the pop-up menu or double-click the Application. Ensure the Application being installed has the same database type as the Metadata Repository, otherwise installation will fail.
- Once this menu option is chosen, enter the ODBC data source and logon to the meta repository and click **OK**.

Notes:

Applications created in 3D cannot be loaded into the latest version of RED if they were created in WhereScape 3D before version 2.8.0.0. To complete the application load process; export the XML file from the latest version of 3D **OR** complete the application load process in a version of RED earlier than 6.8.6.3.

Teradata

1. Teradata Applications


- When loading an application into Teradata, the TDPID will be tested. If the TDPID test fails at this stage, a dialog will appear asking you to enter the correct TDPID. Click Test and Use after entering the TDPID and relevant credentials. If you skip the test and provide an invalid TDPID, native loads will not work in WhereScape RED. Teradata native loads use bteq which connects natively to the database using its own internal protocols without using the ODBC driver. Therefore, ODBC settings are not relevant in this process and a valid Teradata TDPID is required to load application procedure and scripts successfully using native load.
- After the TDPID check, an additional dialog is displayed for selecting the metadata repository database. Select the database and click OK.

Oracle

2. Oracle applications

When loading an application into Oracle, the TNS Name will be tested. If the TNS Name test fails at this stage, a dialog will appear asking you to enter the correct TNS Name.

Click **Test and Use** after entering the TNS Name. If you skip the test and provide an invalid TNS Name, native loads will not work in WhereScape RED.



TNS Service Name

Performing a Native Load of data into an Oracle Database requires a valid TNS Service Name. Failure to supply a valid TNS Service Name will result in errors during the data load portion of the Application Installation, and possibly a malfunctioning Data Warehouse.

Please enter a TNS Service Name (max 64 characters):

ORCL


Login name:

dssdemo

Password:

Test and Use Skip Test and Use Cancel Install

A list of all the objects in the application is displayed in the right pane. Each object is identified as either new to the metadata, or as a replacement for an existing object. For example:



Setup Administrator

47 Object/s will be created.
45 Object/s will be replaced.
You may cancel at this point and review the objects to be replaced and/or added.
If you then wish to proceed a right mouse menu option is available to proceed.
Do you wish to proceed now ?

OK Cancel

A window appears after the list has been displayed, advising of what is to occur. You may cancel the application load at this point and review the objects to be replaced. The load can then be continued by using the right-click menu option when positioned over any object.

Click **OK** to proceed with the application load. A new window appears providing options for the application load:

Load Application ×

- Metadata Options
- Data Warehouse Options
- Procedure
- Host Script

Application Files	
Application Identifier	SQLTest
Application Version	tutorial_4
Application Database Type	SQL Server
General Options	
<input type="checkbox"/> Use Native Load for metadata Procedures and Scripts	False
<input type="checkbox"/> Map Tablespaces/Filegroups to the same name	True
<input type="checkbox"/> Apply Group/Project/Object Relationships	True
<input type="checkbox"/> Generate load scripts and update routines for objects	True
<input type="checkbox"/> Enable auto generation of indexes	True
Existing Parameters will be	Renamed
User Name	
Permanent Stage Table Options Hidden	False
Connections	
<input type="checkbox"/> Map Connection References to the same name	True
<input type="checkbox"/> Map Target References to the same name	True
<input type="checkbox"/> Add Connections as required	True
Jobs	
Assign Jobs to User	WhereScape Documentation
Existing Jobs will be	Renamed

Application Files

The application load is ready to proceed.
The metadata repository will be updated with information stored in the application.
Once the metadata repository has been updated a number of additional actions can be undertaken as selected.

Save Settings
Load Settings
Default Settings
Load With Row Counts
Load Without Row Counts
Cancel

If you click **OK**, the objects are inserted into the metadata.

Metadata Options

<input type="checkbox"/> Application Files	
Application Identifier	SQLTest
Application Version	tutorial_4
Application Database Type	SQL Server
<input type="checkbox"/> General Options	
Use Native Load for metadata Procedures and Scripts	False
Map Tablespaces/Filegroups to the same name	True
Apply Group/Project/Object Relationships	True
<input type="checkbox"/> Generate load scripts and update routines for objects	True
Enable auto generation of indexes	True
Existing Parameters will be	Renamed
User Name	
Permanent Stage Table Options Hidden	False
<input type="checkbox"/> Connections	
<input type="checkbox"/> Map Connection References to the same name	True
Map Target References to the same name	True
Add Connections as required	True
<input type="checkbox"/> Jobs	
Assign Jobs to User	WhereScape Documentation
Existing Jobs will be	Renamed

Application Files

Option	Description
Application Identifier	The application identifier is a four character code used to uniquely identify the application. This identifier is used in the naming of the files that are created to contain the application data.
Application Version	The version is a character string that provides a version number for reference purposes. This version number is displayed when applications are being loaded and is used in the naming of the files that are created to contain the application data. As such, it must contain characters that are valid in a Windows file name.
Application Database Type	The database type from which the application was built. An application can only be loaded into a metadata repository running on the same database type from which the application was created—(e.g. An application created from Oracle database cannot be loaded into a SQL Server metadata repository).

General Options

Option	Description
Use Native Load for Metadata Procedures and Scripts	This option causes the metadata for procedures and scripts to be loaded into the target metadata repository, using the target repository's load utility instead of ODBC. This can have significant performance advantages when loading large applications, when loading applications into a slow target database or over a slow network. The loaders used are: SQL*Loader for Oracle, bcp for SQL Server and BTEQ for Teradata data warehouses.
Map Tablespace/Filegroups to the same name	Every table in Oracle is located in a tablespace . SQL Server tables may be in filegroups . If this option is set, existing tablespaces and filegroups in the target data warehouse database will automatically be matched to their same ones on the source repository.

Option	Description
	<p>If the tablespace/filegroup does not exist in the target data warehouse database, a Tablespace selection window pop-ups so a tablespace/filegroup can be selected. This window appears once for each tablespace/filegroup that cannot be matched.</p> <p>Note: This option is not available for Teradata.</p>
Apply Group/Project/Object Relationships	If this option is set to True, the project group relationships are updated in the target data warehouse database.
Generate load scripts and update routines for objects	<p>If this option is set to True, the deployment will include the generation of load scripts and update routines for the table objects, but only if:</p> <ul style="list-style-type: none"> the code generation is template based. a default load script and update routine template is set for the object type in the target connection the default build options satisfy the requirements of the default template. <p>Refer to the Connection Properties and Rebuilding Update Procedures sections of the RED User Guide for details.</p> <p>This option can be used by Data Vault customers who utilize WhereScape 3D to import table objects into RED via deployment applications. This setting is enabled by default for 3D applications so that when the objects are loaded into RED during deployment, their initial update scripts or routines are also generated. This option defaults to 'OFF' during the deployment of applications generated by RED.</p>
Enable auto generation of indexes	If this option is set to True, the deployment will also include the generation of indexes for the table objects after the update routines are generated.
Existing Parameters will be	<p>Enables you to specify the action for existing parameters. The options are:</p> <ul style="list-style-type: none"> Updated/Overwritten Retained Renamed
User Name	Enables you to enter a username which is included in the versioning comments.
Permanent Stage Table Options Hidden	<p>Enables you hide the Permanent Stage Table object options in the window. Save Settings must be used to save the option selection. This window does not refresh upon changing this option.</p>

Connections

Option	Description
Map Connection References to the same name	<p>During deployment, objects need to be associated with a Connection. Setting this option to False causes the user to be prompted to choose a Connection for each object.</p> <p>Setting this option to True causes the WhereScape RED Setup Administrator to compare the name of all existing connections within the Data Warehouse with the Connection name defined in the deployment application for the current object. If the names match, then the WhereScape RED Setup Administrator deploys the object to this Connection. If no Connection name matches, then the user is prompted to choose a Connection.</p>

Option	Description
Map Target References to the same name	<p>During deployment, objects need to be associated with a target within a Connection. Setting this option to False causes the user to be prompted to choose a Target for each object.</p> <p>Setting this option to True causes the WhereScape RED Setup Administrator to compare the name of all existing Targets within the Connection that has been either selected by the user or matched automatically.</p> <p>If the names match, then the WhereScape RED Setup Administrator deploys the object to this Target. If no Target name matches, then the user is prompted to choose a Target. Choosing a Target involves choosing a Connection—the WhereScape Setup Administrator automatically selects a Connection. If required, the WhereScape RED Setup Administrator selected Connection can be overridden using the GUI.</p>
Add Connections as required	If this option is set to True, all Connection objects included in the application that do not exist in the Target metadata repository which are used by objects in the application will be added to the Target metadata repository.

Jobs

Option	Description
Assign Jobs to User	All jobs in the WhereScape RED scheduler belong to a user. If this option is marked as true, the user name specified in the User name for any jobs added by the application drop-down is set as the user name of all jobs loaded by the application. If the specified user name does not exist, it is then created.
Existing Jobs will be	<p>Enables you to specify the action for existing jobs.</p> <p>The options are:</p> <ul style="list-style-type: none"> • Updated/Overwritten • Retained • Renamed

Data Warehouse Options

Data Warehouse Options	
Apply Metadata Changes to Data Warehouse Objects	True
Log Metadata DML and Data Warehouse DDL to a File	True
DDL File	C:\Users\Documents\WhereScape\app_SQLTest_example_1_ddl.sql
DDL File Statement Terminator	;
Terminate lines with carriage return as well as new line	True
Select encoding for DDL and Procedure files	UNICODE
Compile New and Changed Procedures	True

Option	Description
Apply Metadata Changes to Data Warehouse Objects	If this option is marked as True, the changes contained in the application are applied to the metadata according to the options selected for each object type.
Log Metadata DML and Data Warehouse DDL to a File	<p>If this option is marked as True, the changes contained in the application are written to a file.</p> <ul style="list-style-type: none"> • DDL File - Option to enter or select the file name/path for the DDL file. • DDL File Statement Terminator - Option to specify the statement terminator. • Terminate lines with carriage return as well as new line - Option to terminate DDL file lines with a carriage return, as well as a new line. • Select encoding for DDL and Procedure files - Option to specify the

Option	Description
	encoding to be used for the DDL and Procedure files—options are UNICODE, ASCII or UTF-8.
Compile New and Changed Procedures	If this option is marked as true, then all procedure objects loaded by the application load are compiled in the target data warehouse database. Note: Depending on the type of database, invalid procedures may not compile.

Data Warehouse Table/View Options

Load Table	
New Load Tables will be	Created
New Load Tables will be Versioned	False
New Load Table Indexes will be	Created
Existing Load Tables will be	Recreated
Existing Load Tables will be Versioned	True
Existing Load Table Indexes will be	Recreated
New Table Default Load Type if not set in Source Connection	Script based load
New Table Default Load Script Connection if not set in Source Connection	Windows
New Table Default Load Script Template if not set in Source Connection	wsl_common_powershellscript_stub

For each table and view object loaded by the application load, it is possible to specify whether the metadata changes should be applied to the data warehouse table or view; and to the indexes on these objects. The change action can be specified by object type. New objects can have a different action to existing objects of the same type. Possible actions are:

- **Created** - available for new tables and indexes of any object type
- **Recreated** - available for existing tables and indexes of any object type
- **Altered** - available for existing tables and indexes of most object types (not available for load tables or views)
- **Nothing** - available for all new and existing object types and indexes.

The following additional settings can be configured when importing Load table objects from 3D to RED:

- New Table Default Load Type, if not set in Source Connection
- New Table Default Load Script Connection, if not set in Source Connection
- New Table Default Load Script Template, if not set in Source Connection

Note:

The above default settings are only applied for new Load table objects, if these attributes are not defined in the Source Connection. They only apply for new Load table objects and Connections from 3D.

This window also enables you to set whether or not new or existing objects are to be versioned. Set to **True** to use versioning, else set to **False**.

Stage Table	
New Stage Tables will be	Created
New Stage Tables will be Versioned	False
New Stage Table Indexes will be	Created
Existing Stage Tables will be	Recreated
Existing Stage Tables will be Versioned	True
Existing Stage Table Indexes will be	Recreated
Alter allows columns to be dropped	False
Allow alter table processing with noncompliant DDL	True

Other options:

- **Alter allows columns to be dropped** - This option enables you to set whether or not columns are allowed to be dropped by object type, for tables being altered. Set to **True** to allow columns that are not in the metadata, to be dropped; else set to **False**.
- **Allow alter table processing with non-compliant DDL** - This option is used for custom database targets and sets whether or not to allow DDL statements that do not use a substitutable format for the table name to be used during validation, and subsequent alter table processing. Default setting is **True**. The DDL statements are set in the template that is defined in the custom database Connection properties (**Connection > Target Settings > Default Table Create DDL Template**) in RED. Refer to Connection Target Settings for Custom Database in the RED User Guide for details.

WARNING:

Setting this option to TRUE can lead to the DDL being run against the actual data warehouse table.

The above options applies to Stage, Permanent Stage, Dimension/Model, ODS, Normal, Fact and Aggregate tables.

Object action settings may be saved and reloaded later for another application using the **Save Settings** and **Load Settings** buttons. Supplied default settings may also be loaded by clicking the **Default Settings** button.

The Connection Build Window

The **Connection Build** window appears when the connection used by an imported table does not exist in the destination Data Warehouse.

The **Connection Build** window is displayed if the following criteria are met:

- If the connection the table uses is included in the exported files, but the **Add Connections as required** setting is disabled, the window is displayed with the **Add Connection** button. Clicking the **Add Connection** button adds the connection included in the exported files to the destination Data Warehouse.
- If the connection the table uses is not included in the exported files, the window is displayed without the **Add Connection** button. The user is required to select an existing connection in the destination Data Warehouse.

Tip:

If a new connection is added then it will need to be modified to match the database and user names of the new environment, on the relevant **Connection Properties**' dialog in WhereScape RED.

Loading Applications with Targets

When importing tables that contain Targets which do not exist in the destination Data Warehouse, users can select existing Targets from the list or add new ones, using the **Add Connection/Target** in the **Resolve Target** window, see the topic below for more information.

Adding Connections and Targets

On the **Add Connections and Targets** screen, click the **Add** button to add your desired connection.

Setup Administrator recognizes you are trying to import a table that references a specific connection type and that option will be selected by default in the **Connection Type** drop-down list. In the example below, Setup Administrator recognizes a tabular table imported from a Microsoft Analysis Services 2005+ connection and selects it.

Type in the connection details and then click **OK** to create the connection.

Create Connection for dim_customer_tabular

The object loaded from the exported Application requires a Database of type "Tabular"

Please define a connection to a Database of this type.

Connection: Tabular Cubes

Connection Type: Microsoft Analysis Server 2005+

Server Mode: Tabular

Server Name:

User ID:

Password:

OK Cancel

The Filegroup /Tablespace Selection window

Filegroups/Tablespaces may need to be manually remapped to the corresponding Filegroup/Tablespace available to the metadata repository.

A window is displayed for each Filegroup/Tablespace encountered that is not automatically mapped (refer to Filegroup/Tablespace options above).

Filegroup Selection

Objects which are being imported contain filegroup names which need to be resolved to the new repository. Please select the new filegroup.

Old Filegroup: LoadTables

New Filegroup: PRIMARY

OK Cancel

The **New Filegroup** drop-down lists all filegroups visible to the repository.

A window appears when the application load has been completed. The full results should be reviewed by scrolling back, or you can right-click and click **Excel It** to send the results to Microsoft Excel.

Computer Setup	Application Installation	
Oracle	Object	Status
Metadata Repository	fact_forecast_idx_3	Index created
Scheduler	fact_forecast_idx_A	Index created
Application	fact_sales_analysis	Table created
Application Load	fact_sales_analysis_idx_1	Index created
Change Application Directory	fact_sales_analysis_idx_2	Index created
List applications in Repository	fact_sales_analysis_idx_3	Index created
	fact_sales_detail	The table fact_sales_detail already exists, and contains 21 rows of data
	agg_sa_customer	Table created
	agg_sa_customer_idx_1	Index created
	agg_sa_customer_idx_2	Index created
	agg_sa_product	Table created
	agg_sa_product_idx_1	Index created
	agg_sa_product_idx_2	Index created
	dim_order_date	The view dim_order_date already exists, and contains 0 rows of data
	dim_order_date	View (re)created
	dim_ship_date	The view dim_ship_date already exists, and contains 0 rows of data
	dim_ship_date	View (re)created
	get_dim_customer_key	Compiled
	update_dim_customer	Compiled
	get_dim_date_key	Compiled
	update_dim_date	Compiled
	get_dim_order_date_key	Compiled
	get_dim_product_key	Compiled
	update_dim_product	Compiled

Creating and Loading Applications from the Command Line

It is possible to create and load applications from the command line by running a batch file. The WhereScape RED Application directory contains an example batch file `WSL_Application_Create_Restore_Point_and_Load.bat` for creating and loading.

If you right-click this file and select **Edit** you will see the steps outlined, as well as the details on the options available.

The first step **creates** a restore point application (R) based on objects about to be loaded. This process calls the command line functionality of RED and creates the application file.

The second step **loads** an application (A) into a test WhereScape RED repository. It uses an XML Options File to specify various options, calls the command line automation functionality of Setup Administrator and loads the application (A). Ensure that you have already created and properly defined the XML Options File. Refer to [XML Options File for Application Loads](#) for details.

The WhereScape RED Application directory contains example XML files:

- `WSL_Application_Load_SQL.xml` for SQL Server
- `WSL_Application_Load_ORA.xml` for Oracle
- `WSL_Application_Load_TER.xml` for Teradata

The tags in the XML Options File need to be edited because the login/connection details, etc. need to be set. Refer to [XML Options File for Application Loads](#) for details.

The Batch Application Create options and the Batch Application Load options (described below) are listed at the end of the batch file. The values for these variables also needs to be customized before running this file.

The process typically involves the following steps:

1. Create an application (A) in RED containing your data warehouse changes.
2. RUN `WSL_Application_Create_Restore_Point_and_Load.bat` from the command line; which creates a restore point application (R) and applies application (A) to a test WhereScape RED repository.
3. If the changes are incorrect, they can be undone by loading the restore point application (R).

Batch Application CREATE Options

The following options are available on RED to create applications.

Option	Description
/BA	Selects batch application create.
/U	ODBC user name.
/P	ODBC password.
/C	ODBC DSN name.
/A	DSN Architecture
/M	meta database for Teradata logon.
/N	RED User name.
/D	Directory to save application files.
/I	New application files identifier.
/V	New application files version.
/AP	Project name - all objects in a Project; and associated jobs.
/AG	Group name - all objects in a Group; and associated jobs.
/ALL	All objects - all objects, jobs and parameters.
/RC	Remove connections - drop all connections from the application.
/RJ	Remove jobs - drop all jobs from the application.
/RP	Remove parameters - drop all parameters from the application.
/AF	Absolute application id file name which restore point is being created for.

If using a trusted connection, the user name and password are not necessary.

Batch Application LOAD Options

The following options are available on Setup Administrator to load applications.

Option	Description
/AL	Select application load.
/AF	Absolute application ID file name.
/LF	Absolute log file name.
/PF	Absolute xml parameter file name.
/SO	Stay open - Setup Administrator does not close after the application has been created. Relevant for /AL LOAD option. Relevant for -QA, -QR, -WS, -QL and -QV application switch options. Not relevant for -QS switch option. For switch options, refer to SQL Server Quick Application for details.

Setup Administrator Process Exit Codes

When installing an application using the command line, the Setup Administrator process returns one value from a set of exit codes from its process when exiting.

After an application install, when the Setup Administrator process exits, users can check the exit codes to determine the cause for a possible problem with the application install.

The set of Setup Administrator exit codes are described below:

Exit Code Name	Exit Code	Description
AdmExitedNormally	0	The user clicked the main window's X button in the top right, the Exit item from the File menu, or the task that ran completed without error.
InternalError	1	An unexpected internal error occurred. The user should contact WhereScape support and supply any relevant log files.
CommandCancelled	2	The user clicked the cancel button from one of the presented dialog boxes, thus aborting the running task.
RequiredParameterMissing	3	One or more required parameters is missing, e.g. a name for the Scheduler, an ODBC DSN, a user name, a password.
OdbcError	4	An error was reported from the RDBMS that Setup Administrator was communicating with.
FileIoError	5	A specified file or directory was unable to be opened, read from or written to.
ServiceControlManagerError	6	An error was reported from the Windows Service Control Manager. Often, this is because Setup Administrator needs to be run "As Admin" when dealing with the SCM.
OracleCompilationError	7	An Oracle stored procedure has failed to compile.
MetaDataError	8	Metadata was or was not found in the specified RDBMS, or the metadata failed to upgrade, or the metadata is corrupt, or the metadata type mismatches, i.e. trying to import an Oracle application into Teradata metadata.
ItemsCheckedOut	9	In batch mode, if you want to overwrite checked out items, you must explicitly state so by setting the option to true in the settings.
NotLicensed	10	License does not permit objects of a specific type to be imported.

Users can test for these values, using a batch file and take action accordingly.

Below is an example batch file that can be used to check Setup Administrator's exit code.

Example batch file - SQL:

```
@echo off

Adm.exe /AL /AF "app_con_SQLT_base_1.wst" /LF "ImportLog.txt" /PF
"WSL_Application_Load_SQL.xml"

if errorlevel 8 goto MetaDataError
if errorlevel 5 goto FileIoError
if not errorlevel 0 goto ImportError

echo Successfully imported
goto end

:MetaDataError
sendmail -recipient admin@company.com -subject "Import failed" -body "Corrupt meta data found
during application import. Re-install the Data Warehouse"
goto end

:FileIoError
sendmail -recipient admin@company.com -subject "Import failed" -body "ExportedDiagram.xml is
```

```
missing, re-generate it then re-run this process"
goto end

:ImportError
sendmail -recipient admin@company.com -subject "Import failed" -body "Unable to import the
application file ExportedDiagram.xml"
goto end

:end
```

Example batch file - 3D:

```
@echo off
Start /wait /D "C:\Program Files (x86)\WhereScape\Adm.exe" /AL /AF "ExportedDiagram.xml" /LF
"C:\temp\test\ImportLog.txt"
if %errorlevel% equ 8 goto MetaDataError
if %errorlevel% equ 5 goto FileIoError
if not %errorlevel% equ 0 goto ImportError
echo Successfully imported
goto end

:MetaDataError
sendmail -recipient admin@company.com -subject "Import failed" -body
"Corrupt meta data found during application import. Re-install the Data Warehouse"
goto end


:FileIoError
sendmail -recipient admin@company.com -subject "Import failed" -body
"ExportedDiagram.xml is missing, re-generate it then re-run this process"
goto end

:ImportError
sendmail -recipient admin@company.com -subject "Import failed" -body
"Unable to import the application file ExportedDiagram.xml"
goto end


:end
```

Changing the Application Directory

1. In WhereScape's Setup Administrator, click the **Application** tab and then click **Change Application Directory**.




2. Browse and select a new application directory.



Listing Applications

1. In **WhereScape's Setup Administrator**, click the **Application** tab in the left pane and then click **List applications in Repository**.



2. The **List applications in Repository** menu option prompts for a logon to the required metadata repository. Applications are applied to a specific metadata repository. Once logged on a list of the applications that have been installed into that repository is shown. If no applications have been loaded, then the list is empty. An example output is as follows:

List Installed Applications				
App Id	Name	Version	Status	Date installed
SQLT	WhereScape Tutorials (SQL Server)	tutorial_2	Completed	2007-02-13 17:32:16.257

This example shows that the tutorial_2 application has been loaded into the metadata.

Testing Applications

A testing application set consists of a Procedure and an XML script and provides the ability to define a series of tests against data warehouse objects; either comparing them to an expected value or to the results of a query.

The XML script contains the test definitions. Each test is a new XML node in the XML script and contains a name, a test query, an expected value, or a comparison query.

The procedure simply runs the tests and determines whether the tests are passed or not. This is most likely to be run as a scheduled job within WhereScape RED.

XML Options File for Application Loads

If applications are being loaded using the command line, the saved application load options in the local registry can be outputted to an XML Options File for use in the application load.

Refer to [Creating and Loading Applications from the Command Line](#) for details.

1. To create the options file, click **Create XML Options File** in the left pane.

Tip:

You can also access the **Create XML Options File** from the **Applications** menu.





2. If the load options have not yet been saved into the local registry, a message appears prompting you to select the application to be loaded and to save the load settings for that application.
 - o Type in the location where you want to save the XML Options File in the **XML Options File Name** field.
 - o Type in the details of the **XML Elements** that are added to the destination details of the XML Options File.

Metadata Repository Type	The RDBMS type of the metadata repository.
DSN	The value to be written in the <DSN/> element of the XML Options File.
DSN architecture	The value to be written in the <DSNArchitecture> element of the XML Options File.
User ID	The value to be written in the <UserID/> element of the XML Options File.
Password	The value to be written in the <Password/> element of the XML Options File.

Create Options File ✕

An XML file will be created containing deployment options that were previously saved into the Windows Registry.
Which metadata repository to write into the XML file is required before the operation can begin.





Please provide values for these additional fields:

General	
XML Options File Name	C:\Users\UserA\Documents\WhereScape\WslAppLoadOp
XML Elements	
Metadata Repository Type element	SQL Server
DSN element	WslWarehouse
DSN architecture element	32
User ID element	sa
Password element	*****

Password element
A value to be written into the <Password/> element

3. Click **Create File**, the results confirm that the XML Options File has been created.

Computer Setup	Application Load XML File
Oracle	Results
Metadata Repository	XML file C:\Users\UserA\Documents\WhereScape\WslAppLoadOptions.xml created.
Scheduler	
Application	
 Application Load	
 Change Application Directory	
 List applications in Repository	
 Create XML Options File	

Upgrading WhereScape RED

WhereScape Versions

WhereScape RED has a four part version number normally shown as xx.xx.xx.xx. An example of this may be 8.3.1.0. The first number represents the major release. The second number represents the metadata repository version. The third and fourth numbers relate to application specific releases.

From the example above, we see that the current version is version 8 of WhereScape RED. We are on version 8.3 of the metadata repository.

Metadata Changes

A change from a 8.2.. release to a 8.3.. release would indicate a change in the metadata tables. All metadata changes are non-destructive. They simply add new columns or new meta tables. In this way they can be applied without harming an existing metadata repository. The impact of a metadata change is that the associated applications (namely the RED executable, the Scheduler, security module, etc.) needs to be at the same metadata version. Therefore, an 8.2.1.0 version of RED may not successfully run against a version 8.3 metadata repository.

Application changes

The final two numbers in the version represent application releases. Applications are deemed to be all of the executable images supplied with WhereScape RED as well as the UNIX scheduler scripts and the stored procedures. Application changes reflect enhancements and bug fixes. A change in the first number indicates a major enhancement in one of the application components.

Upgrading RED

Notes:

- Ensure that you have made a backup your metadata before performing the upgrade.
- Ensure you also upgrade the WhereScape RED scheduler. The old scheduler must be stopped prior to the upgrade and a new scheduler must be setup after RED is installed.

Upgrading WhereScape RED consists of the following steps:


1. Allow any active jobs to complete. Halting active jobs will allow running tasks to complete with no new tasks starting. Aborting active jobs will kill any running tasks and stop running jobs.
2. Stop all schedulers. Windows schedulers can be stopped with WhereScape's Setup Administrator. To stop a UNIX or Linux scheduler, kill the active scheduler process and comment their crontab entries (to stop the scheduler re-starting itself).
3. Close any WhereScape programs that are running on your machine.
4. Back up your metadata.
5. Install the new version of RED on your machine.
6. In RED Setup Administrator, select the Validate Metadata Repository option. This function may re-compile existing or create new metadata procedures; metadata tables may be altered, or new tables created.
7. When performing an upgrade of RED:
 - o Click **OK** when prompted to validate metadata tables.
 - o Click **Yes** when prompted to re-create metadata views.
 - o Click **Yes** when prompted to re-compile metadata procedures.

Warning

If the above steps are not all completed during an upgrade, the metadata may be left in an inconsistent state.


8. For Oracle metadata updates, see the note below on **recompiling Oracle invalid procedures** during a RED upgrade.
9. Back up your metadata again (just in case).
10. If using a UNIX or Linux scheduler and this is a major application enhancement, then rename the wsl/bin directory to say wsl/bin_versionxxxxxx. Create a new bin directory and ftp over the files under the UNIX directory (see the main install instructions). Change the protections on the files (chmod 750 *.sh).
11. Restart all schedulers. Windows schedulers can be restarted with WhereScape's Setup Administrator. For any UNIX or Linux schedulers, uncomment any commented out crontab entries— this is enough to restart the schedulers.
12. Restart any halted or aborted jobs.

Notes:

- i. There are different versions of the scripts for each database and for UNIX versus Linux. You should also be looking in the sub directory with the highest version number.  When using a UNIX/Linux scheduler for Oracle, it is recommended that users copy the new meta_backup_680.sh file to use Datapump's expdp/impdp instead the deprecated exp/imp tools.
This version uses the data pump export executables expdp/impdp. It assumes that the scheduler and the Oracle database reside on the same server.
- ii. Metadata tables do not change between minor releases, but metadata procedure often and usually do change.
- iii. RED will not let you sign into an old repository version using a newer version of RED.
- iv. RED will let you sign into a new repository version using an older version of RED but it will warn you that this may potentially cause issues.
- v. It is very important when using the Windows scheduler to have the installed RED version on the scheduler server EXACTLY matching the stored procedures.
- vi. Side by side installations are possible (two versions in two directories on the same machine), but be careful with schedulers. If you install the new version of RED in a new directory, you must remove and reinstall all Windows schedulers in order for the scheduler(s) to use the new version of RED.
- vii. As a general rule, the UNIX and Linux scheduler scripts, metadata tables/procedures and RED front end should all be in sync.
- viii. If the scripts for the UNIX or Linux scheduler have changed, you should replace files in your old and new shell scripts in the WhereScape Program Files directory and see if any have changed.

Oracle Invalid Procedures

When validating an Oracle Metadata Repository, select the **Recompile any invalid procedures** check box to have any invalid user procedures recompiled during a metadata validate.




Checking the Unix Connection

Note

This section applies to Oracle data warehouses only.

1. To check the UNIX connection, click the **Computer Setup** tab and then click **Check Unix Connection**.



WhereScape RED can allow the user to browse a Unix file system and utilize the drag and drop functionality to setup the loading of files from a Unix file system. It can also perform interactive file loads. To facilitate this and to obviate the need to port code to every Unix environment the Telnet protocol is used for the Unix connectivity.


This step is not necessary for the successful running of a Unix based data warehouse environment. As mentioned above it is provided to simplify the process of setting up the loading of Unix files. This step is totally unnecessary for a Windows based data warehouse environment.

If you want to use these Unix drag and drop assistants, then consult the *WhereScapeRED User Guide* for an explanation of Unix connections and perform the following tasks:


1. Identify a Unix user that allows direct logon to a Unix shell prompt without passing through a menu system.
2. Ensure that the Unix user has the Oracle 'sqlldr' program in the path after a normal logon. If not, then interactive loads will not be possible. Scheduled loads should still function correctly.
3. Complete the dialog box presented, specifying the Unix user and password identified in step (1).
4. Click **OK** to proceed. A timeout of 20 seconds is enabled, so that if connection is not achieved within that time the process will terminate. The Telnet window will be displayed to assist in debugging any problems. It will be closed on completion or timeout.
5. Review the results and attempt to address any problems. A file called 'WsITelnet.log' is created in the installation directory containing the full dialog of the connection attempt. The message 'Telnet connection worked. All OK' will be displayed if the connection worked. If successful record the parameters used as these will need to be defined when setting up a Connection within WhereScape RED itself. If a connection cannot be achieved, then remove all reference to a username and password from the file mentioned above and mail it to support@wherescape.com.

Testing an ODBC Source

1. To test an ODBC source, click the **Computer Setup** tab and then click **Test ODBC Source**.



2. Select the **ODBC connection** from the drop-down list and enter the **User Name** and **Password**.
 - o Click **OK**.




3. If the logon using the ODBC connection was successful, the following message is displayed.

Computer Setup	Test ODBC connection
<p data-bbox="402 212 467 268"></p> <p data-bbox="305 281 568 310">WhereScape RED License</p> <p data-bbox="410 321 459 378"></p> <p data-bbox="305 390 565 420">Check Windows Version</p> <p data-bbox="410 430 459 487"></p> <p data-bbox="331 499 542 529">Check Odbc Drivers</p> <p data-bbox="410 539 459 596"></p> <p data-bbox="289 606 584 636">Validate / Add Odbc Source</p> <p data-bbox="410 646 459 703"></p> <p data-bbox="310 716 563 745">Check Unix Connection</p> <p data-bbox="402 753 467 810"></p> <p data-bbox="337 823 535 852">Test ODBC Source</p>	<p data-bbox="667 212 737 241">Result</p> <p data-bbox="662 247 1354 277">Sales logged on using Odbc connection Sales successfully. All OK</p>

Validating a Meta Repository

1. To validate a Metadata Repository, click the **Metadata Repository** tab and then click **Validate Metadata Repository**.



This option validates the version of the meta tables installed in the specified SQL Server database, Oracle schema, or Teradata Database/User. If requested it goes on to validate the tables, sequences and procedures against the installation media. A validate can be run at any stage to confirm that all tables and procedures are up to date and that the procedures are in a compiled and valid state. This option can be used to recompile a procedure that has become invalid. This option must be used when installing a new version of RED and for SQL Server database to recompile all procedures.


If a mismatch is found or a procedure is found to be invalid, the user is given the option of updating the metadata. If chosen, the metadata will be upgraded to the latest version.

Note:

Ensure the scheduler is not running and no users are accessing the metadata before doing an upgrade.

Oracle Invalid Procedures

When validating an Oracle Metadata Repository, ensure that the **Recompile any invalid procedures** option is selected to recompile any invalid user procedures during a metadata validate.



Validating a Metadata Repository using the Command Line

It is possible to Validate the Metadata Repository, using the Command Line by running a batch file.

This process can be used for all metadata database types: it validates the tables and alters or creates/copies any tables that require changes.

All the process steps are logged to a file: **My Documents\WhereScape\WhereScape_quick_validate.log**.

During this process:

- All Teradata metadata views are recreated
- Oracle sequences and procedures are validated and updated if required
- All non-Oracle procedures are recompiled
- All metadata indexes are recreated
- Any Oracle non-metadata procedures that are invalid are compiled
- Finally, the metadata version in ws_meta_tables.mt_version is updated

To have a metadata repository validated from the command line, create a batch file using the following batch application quick validate options and check the example below:

Batch Application Quick Validate options

```
ADM -QV
-SN DSN
-SL LoginId
-SP Password
```

```
-DS.....  
 //SQLServer Dimension filegroup  
 //Teradata - not used  
 //Oracle Dimension Table Tablespace  
  
-IS.....  
 //SQLServer Dimension Index Filegroup  
 //Teradata - not used  
 //Oracle Dimension Index Tablespace  
  
-MS.....  
 //SQLServer Metadata Filegroup  
 //Teradata Metadata Repository Database  
 //Oracle Metadata Repository Tablespace
```

Example

The following example validates an Oracle repository named WslWarehouse_ORA, using a connection with username dssdemo and password wsl.

It recreates the Oracle Dimension Index Tablespace, validates the Oracle Metadata Repository Tablespace and validates/updates the Oracle Dimension Table Tablespace, recompiling any procedures that may be invalid, during the validate process.

```
@echo off  
cd "c:\Program Files (x86)\wherescape\  
adm -QV -SN WslWarehouse_ORA -SL dssdemo -SP wsl -IS RED_METADATA -MS RED_METADATA -DS  
RED_METADATA  
exit
```

Scheduler Installation and Configuration

The Install Scheduler option installs and starts a copy of the WhereScape Windows scheduler. The scheduler runs as a system service and can also be maintained through the normal Windows services functions.

This chapter covers both Windows and UNIX/Linux scheduler installation and maintenance.

Diagram Overview of RED and Scheduler Database Access


The following diagrams in this chapter provide an overview of how WhereScape RED and the scheduler access SQL Server, Oracle and Teradata and databases.

SQL Server Diagram Overview

The following diagram provides an overview of how WhereScape RED and the scheduler access a **SQL Server** database.

The scheduler makes use of the ODBC layer to perform the routine tasks involved in scheduling and running jobs. WhereScape RED and the scheduler can also use SSIS to load data into SQL Server.

For file or script-based loads, the scheduler actions the load on the host system using **BULK INSERT**.




Oracle Diagram Overview

The following diagram provides an overview of how WhereScape RED and the scheduler access an **Oracle** database.

The scheduler makes use of the ODBC layer to perform the routine tasks involved in scheduling and running jobs. When loading data from an ODBC source the scheduler can either use the **ODBC layer** or the **Oracle Direct Path** load facility.


For file or script-based loads, the scheduler actions the load on the host system utilizing **Oracle SQL* Loader**.



Teradata Diagram Overview


The following diagram provides an overview of how WhereScape RED and the scheduler access a Teradata database.

The scheduler makes use of the ODBC layer to perform the routine tasks involved in scheduling and running jobs. WhereScape RED and the scheduler can also use the **TPT ODBC operator** to load data into Teradata. For file or script-based loads, the scheduler actions the load on the host system using **fastload**, **multiload** and **TPT** (load and update operators).



Installing a Windows Scheduler

1. In **WhereScape's Setup Administrator**, click the **Scheduler** tab in the left pane and then click **Install Scheduler**.



Notes:

- To install or maintain the Scheduler, you need to run RED's Setup Administrator as an Administrator.
- A Windows scheduler must be run as either the system service account or as a user with administrator privileges in Windows.

2. The **Windows Scheduler Definition** window appears. (The windows below show SQL Server, Oracle and Teradata scheduler definition examples).

For configuration settings specific to each database, please see the field description below:



Example:

Windows Scheduler Definition

Unique Identifier (e.g. SID_user): Wslw/warehouse

Scheduler Name (e.g. WINnnnn): WIN0001

Service Display Name: WhereScape WslwWarehouse

Service logged on under User: System Account

Work Directory: C:\ProgramData\WhereScape\Work\

Log File: C:\ProgramData\WhereScape\Scheduler\WslSched_WslwWarehouse.log

Poll Interval (default 30) seconds: 30

Log Level (0=none, 9=debug): 2

Direct Path Load or ODBC: Odbc sql load

TNS Service (Oracle):

ODBC Connection: WslwWarehouse

Database User id: Wslw/warehouse

Database Password: [masked] Password is TD/wallet string

MetaData Schema (DB2):

MetaData Database (Teradata):



Example:

Note:

The WhereScape Windows scheduler for Oracle requires the Oracle client 11.2 or later software. The Oracle client software must be a close version match to the Oracle Database version—that is, the same major release or one release either side.

Windows Scheduler Definition

Unique Identifier (e.g. SID_user): ORCL_dssdemo

Scheduler Name (e.g. WINnnnn): WIN0001

Service Display Name: WhereScape ORCL_dssdemo

Service logged on under User: System Account

Work Directory: C:\ProgramData\WhereScape\Work\

Log File: C:\ProgramData\WhereScape\Scheduler\WslSched_ORCL_dssdemo.log

Poll Interval (default 30) seconds: 30

Log Level (0=none, 9=debug): 2

Direct Path Load or ODBC: Direct Path load

TNS Service (Oracle): ORCL

ODBC Connection: WslWarehouse

Database User id: dssdemo

Database Password: [masked] Password is TDWallet string.

MetaData Schema (DB2):

MetaData Database (Teradata):



Example:

Windows Scheduler Definition

Unique Identifier (e.g. SID_user): Teradata

Scheduler Name (e.g. WINnnnn): WIN0001

Service Display Name: WhereScape Teradata

Service logged on under User: System Account

Work Directory: C:\ProgramData\WhereScape\Work\

Log File: C:\ProgramData\WhereScape\Scheduler\WslSched_Teradata.log

Poll Interval (default 30) seconds: 30

Log Level (0=none, 9=debug): 2

Direct Path Load or ODBC: Odbc sql load

TNS Service (Oracle):

ODBC Connection: TD_15_00

Database User id: WslWarehouse

Database Password: Your TD Wallet String or Password Password is TDWallet string.

MetaData Schema (DB2):

MetaData Database (Teradata): dssdemo

Unique Identifier

Each scheduler requires a unique name, this unique name is the name by which the service is referenced.



Possibly the database name and user, e.g. WslWarehouse_sa



Possibly the SID and user, e.g. ORCL_dssdemo



Possibly the environment name and metadata owner, e.g. prod_dssdemo

Scheduler Name

When scheduling a job with WhereScape RED it is possible to assign the job to a specific scheduler. Each scheduler should therefore have a unique name. The default name is WIN0001. Most users change this to be the scheduler machine's name followed by a number, e.g.: DWHP01, where DWHP is the name of the windows scheduler server.

Service Display Name

This field displays the name that the scheduler will appear under when viewed through the Windows services. It is a combination of the string 'WhereScape' and the unique identifier.

Service Logged on Under User

This is the name of the Windows local user account that the scheduler service will use when logging on. The default setting is System Account, also known as the Local System service account. To set the scheduler to use a Windows domain user account with a password, use the Service Account option from the right-click menu. If a domain user account is specified then the contents of this field (on the Windows Scheduler Definition dialog) are ignored.

Note:

A domain user account requires the log on as a service privilege, in order for it to work. This is assigned automatically when setting the log on account, using the Services console in Windows.

Work Directory

The directory used to store some temporary files created by the scheduler.

Tips:

Two schedulers must not use the same work directory. Setting Log Level 9 creates an additional detailed log file for each thread of each job that is run.

Log File

The full path for this scheduler to write a log file. The log file contains information on the scheduler service, it does not contain information about individual job tasks run by the scheduler. This file may become large if log level 9 is set.

Poll Interval

This defines the frequency of the scheduler polling the database, looking for work. The default is 30 seconds. If set to a very low interval such as 1, then the impact on the database may be noticeable.

Log Level

This defines the level of detail written to the log file by the scheduler service. This should be left at the default level unless requested by WhereScape Support.

The following logging levels are available:

- 0 = log no information
- 1 = log fatal errors only
- 2 = log major events (default)

- 3 = log major events and write ODBC Load statistics to the audit log in the database
- 9 = full debug information

Direct Path Load or Odbc Load



This should always be ODBC sql load for SQL Server and Teradata schedulers.



When using an Oracle repository, this option determines the method used by the scheduler to insert data; when using the ODBC Load type.

Odbc sql load: When this option is selected, the scheduler always load data using the standard ODBC driver method.

Direct Path load: When this option is selected, the scheduler attempts to load data using the Oracle Direct Path method, via the OCI library. If it is unable to use the Direct Path method, the scheduler will revert to using the standard ODBC driver method.

Direct Path ODBC loads are considerably faster and so this option should be set to **Direct Path load** in most situations.


Note:

Once a scheduler service has been created, this option cannot be changed. To change the scheduler from **Odbc sql load** to **Direct Path load** or vice versa, create a new scheduler service and remove the old one.

TNS Service



This is not required for SQL Server or Teradata schedulers.



If you select the Direct Path load option from the Direct Path load or ODBC drop-down-list, enter the database server as defined in the tnsnames.ora file on this field. Normally this will be the same name as entered for the 'server' in an ODBC source definition.

ODBC Connection

The ODBC connection field requires the ODBC source name that provides a connection to the data warehouse system. The scheduler uses ODBC to connect to the data warehouse.

Database User Id

For Windows Authentication, leave this field empty. For SQL Server Authentication, enter a database username.

Database Password



For Windows Authentication, leave this field empty. For SQL Server Authentication, enter the password for the database username entered in the **Database User Id** field.



The password for the User the Scheduler will use when connecting to the data warehouse database.



The password or Teradata Wallet String for the User the Scheduler will use when connecting to the data warehouse Teradata database.

Metadata Database (Teradata)




This is not set for SQL Server/Oracle schedulers.



The Database Name or User Name where the metadata repository is stored. This must be entered for Teradata.


Note:

A Windows scheduler must be run as either the system service account or as a user with administrator privileges in windows.



Error Messages:

The following error message may appear as the scheduler starts. In such an event, the scheduler will not function until the problem is resolved.



This error may be the result of an old version of the Oracle Call Interface (OCI) dynamic link library (dll) being in the path. The WhereScape scheduler requires Oracle client 11.2 or above. This situation can occur when an Oracle product, such as Discoverer is installed. Discoverer may install an older version of the oci.dll file. If it does, its location will be put in the Windows path in front of the 11.2+ client version.

A work-around is to copy an 11.2 or later version of the oci.dll file into the WhereScape program directory. To see if an oci.dll is valid, right-click the file and select properties and then version. A valid oci.dll will have version 11.2 or later.

Installing a UNIX/Linux Scheduler

The Unix scheduler must be manually installed and maintained.

The scheduler consists of a series of shell scripts that are controlled by the cron process. The bulk of the work undertaken by the WhereScape scheduler takes place in the WhereScape procedures within the database. To obviate the need to provide a port to each Unix platform this series of shell scripts are used. They should run with no modification on all Unix platforms and have been tested under Unix offerings from Sun, HP, IBM and Linux.

The Unix scheduler can process every type of load except for ODBC loads, Native ODBC loads and XML loads. It cannot process OLAP Cubes.

Warning:

For UNIX/Linux scheduler processing, the **Encrypt User** and **Password** options in RED's Repository Privacy Settings cannot be used. Encrypt options are only supported when using a Windows scheduler.

Installation

The installation of the Unix scheduler needs to be undertaken by someone familiar with the Unix environment and the running of database processes from Unix. The tasks that need to be undertaken are:

1. Unix User and Shell

Acquire a Unix user name that has access to cron and the database data warehouse environment. A reasonable quantity of disk space is also required if the automated backups of the metadata repository are used. The user should log on to Unix without passing through a menu system if possible. Log on to the user.

This user will need to have a .profile file in "/home/<user>/profile" otherwise ws_sched_check_600.sh will not work. If this file doesn't exist it will need to be created.

The WhereScape scheduler consists of several shell scripts. By default, some of these shell scripts will run in the Bourne shell and some will run in the Korn shell. If Linux is being used, then the Bash shell is used exclusively.

Note:

During setup, it is recommended that the Korn shell be used as the default shell for the user installing the scheduler (or Bash if running Linux).

2. Create directories

Create the following directories (if not already present) to be used by the WhereScape scheduler.

If the directory names are not appropriate and others must be used, then it will be necessary to alter the WhereScape supplied scripts.

- o wsl (top level directory for WhereScape directories)
- o wsl/bin (used to store the WhereScape scripts)
- o wsl/sched (used for the scheduler job and log files)
- o wsl/sched/job (used for the scheduler job files)
- o wsl/sched/joblog (used for the scheduler job logs)
- o wsl/sched/log (used for the scheduler logs)
- o wsl/export (used for the automated exports of the metadata)
- o wsl/expback (used to hold compressed copies of the metadata exports)
- o wsl/log (used for export and archive logs)



Oracle only directories

- o wsl/mon (used for the monitoring process)
- o wsl/mon/db (used for database monitoring scripts and control files)

- o wsl/mon/job (used for job monitoring scripts)
- o wsl/mon/log (used for monitoring log files)

3. Copy supplied Unix files

FTP the scheduler files shipped with WhereScape RED to the wsl/bin directory on the Unix system (use ASCII mode). All files must be copied over. WhereScape RED ships with several different versions of the Unix files for the scheduler. The appropriate version of the files must be copied to the server. The following lists the files shipped:



- o ...\WhereScape\Oracle\Unix\Version_nnn\...
- o ...\WhereScape\Oracle\Linux\Version_nnn\...



- o ...\WhereScape\Teradata\Unix\Version_nnn\...
- o ...\WhereScape\Teradata\Linux\Version_nnn\...

Notes:

There may be several different versions of the scheduler files for a given database and platform (Unix or Linux). These are identified by version numbers nnn. For example, there may be three different folders in: ...\WhereScape\Oracle\Linux: Version_010, Version_410 and Version_560.




...WhereScape\Teradata\Linux: Version_560 and Version_600.


The highest version number script less than or equal to the version of RED in use should always be used.

In the table that follows, the nnn in file names refers to the version number of the script. Some scripts will have 010, some will have 411, others 560 or 680, etc.

A definition of the files follows:

File	Purpose
oraenv (for Oracle) tdenv (for Teradata)	Contains the template of a script for setting environmental variables. This needs to reside in the home directory of the Unix user and must be tailored for the database user and environment. It may be renamed to reflect the actual environment. <ul style="list-style-type: none"> • e.g. oraenv_SID_user for Oracle • e.g. tdenv_TDPID_user for Teradata
crontab	Contains the template of the required cron commands. This file needs to be modified to include the HOME directory of the Unix user, and the name of the environment file. It is then used to update the crontab tables.
ws_start_nnn.sh	Script to start the scheduler. This script is normally called by the ws_sched_check_nnn.sh script and is passed the database environment file name as a parameter.
ws_sched_check_nnn.sh	Script to check that the scheduler is running. This script is normally executed by cron every 20 minutes. If the scheduler is found to be absent it attempts to start a new iteration. By default, the scheduler will terminate if its database is shut down. This script will therefore start the scheduler after a system start-up or a database start-up.
ws_sched_nnn.sh	The actual scheduler script. This script looks for new scheduler jobs every x seconds. The default is every 30 seconds. This script must be modified to change the default behavior. It calls the ws_job_wait_010.sh script to perform the actual checking and initiating of a job. It terminates when ws_job_wait_010.sh returns an

File	Purpose
	error and relies upon cron for a restart.
ws_sched_status_nnn.sh	This script is called by ws_sched_nnn.sh to update the scheduler status in the scheduler metadata. It's a wrapper of the metadata database procedure ws_sched_status (i.e. it calls the database procedure ws_sched_status and returns its results to the calling script).
ws_job_wait_nnn.sh	This script performs the bulk of the work. It is called by ws_sched_nnn.sh on a regular basis. It checks for any job waiting to run. If it locates a job that is ready to run it will create and start a script in the \$HOME/wsl/sched/job directory for each thread of that job. These job threads in turn perform the actual processing and log their results to \$HOME/wsl/sched/joblog. Under normal operation it is not necessary to check or inspect these files.
ws_job_check_nnn.sh	This script is called to check the status of running jobs. It is called by ws_sched_nnn.sh on a regular basis (the interval is defined in ws_sched_nnn.sh). It checks that any job running in the scheduler is actually running in the Unix environment. If a job is not found under Unix, then it is aborted in the scheduler. This scenario can occur as the result of a database or machine crash. If a job abort is required, the results are logged to \$HOME/wsl/sched/log/job_check_'env file name'.log. Under normal operation it is not necessary to check or inspect this file.
cleanup_nnn.sh	This script is normally executed by cron and cleans up files created by the WhereScape scheduler. It deletes old versions of the jobs, job logs, and backups. It will also delete any temporary scripts created in the running of host scripts or file loads from within the scheduler. The location of these temporary scripts is defined within the WhereScape RED Unix Connection object. The default value in the cleanup script is /tmp and this must be altered if a different temporary directory is used for a Connection.
 Oracle only files	
meta_backup_nnn.sh	This script is normally called by the cron process once or maybe more times a day to perform an automated export backup of the metadata tables. It creates a number of command files and a database export in the \$HOME/wsl/export directory named with the date/time of the export.  It is recommended that users copy the new meta_backup_680.sh file to use Datapump's expdp instead the deprecated exp tool. This version uses the data pump export executable expdp. It assumes that the scheduler and the Oracle database reside on the same server.
meta_archive_nnn.sh	This script is normally called by cron once a day to compress and tar the files in the \$HOME/wsl/export directory and relocate them to the \$HOME/wsl/expback directory. This action is performed purely to save on disk space usage.
meta_restore_nnn.sh	This script can be executed to restore from a meta repository backup. It will overwrite any existing metadata. It can be used to restore to a schema/database/user other than the one from which the backup was taken. It does not however restore the WhereScape procedures. If a full recovery or a new user create is required, then the WhereScape metadata install would normally be performed before actioning this restore. If the restore is from an export that has been moved to the expback directory, you will need to uncompress the export and move it and associated files back to the export directory.  It is recommended that users copy the new meta_restore_680.sh file to use Datapump's impdp instead the deprecated imp tool. This version uses the data

File	Purpose
	pump import executable impdp. It assumes that the scheduler and the Oracle database reside on the same server.
 Oracle only files	
ws_mon_nnn.sh	The main monitoring script. This script in turn calls the database and job monitoring scripts to perform the monitoring. By default, the monitor process checks the jobs every 15 minutes and the database every 60 minutes. This script can be edited to change the frequency of the checks if required. Also, a log level of 9 can be set to produce debug logging.
ws_mon_db_nnn.sh	This script checks the database status and if necessary, calls the notify script to notify of a database down. Also checks to see if the criteria for database monitoring has changed and if changed calls the refresh script.
ws_mon_notify_nnn.sh	This script checks that notifications are valid for the day/time and if valid sends a notification.
ws_mon_refresh_nnn.sh	This script refreshes the scripts and command files stored in the mon/db directory. These scripts and command files are used to ascertain the action should the database be unavailable.
ws_mon_jobs_nnn.sh	This script performs the checking of jobs for which monitoring is defined. If a job has a notification required, then this script will issue the notification.
ws_mon_start_nnn.sh	This script starts the monitor process.
ws_mon_check_nnn.sh	This script checks that the monitor process is running. If not running, the script will start the monitor process. This script is normally called via cron every 30 minutes.

4. Set permissions:

Change the permissions on the copied scripts so that they are executable (e.g. `chmod 750 $HOME/wsl/bin/*.sh`).

5. Create an environment file (see below for relevant Oracle or Teradata environment file instructions).



Using the **environment file (oraenv)** as a template and adhering to the variable names within, create an environment file for the database environment and user under which the scheduler is to run.

This file should be located in the \$HOME directory. It may be called anything, but a meaningful name may be `oraenv_SID_user` for a given Oracle scheduler.

Check the users .profile and database environment file to see the normal settings. For Oracle, check to see if the `TNS_ADMIN` variable is in use and if so, include it in the environment file.

Make the following replacements in the environment file:

- o Replace all occurrences of `_HOME_` with the full pathname of your home directory.
- o Replace `_USER_` with the data warehouse database user name.
- o Replace `_PASSWORD_` with the data warehouse database user password.
- o Replace all occurrences of `_SID_` with the SID of the data warehouse database.
- o Replace all occurrences of `_ORAHOME_` with the full pathname of the Oracle home directory.



Using the **environment file (tdenv)** as a template and adhering to the variable names within, create an environment file for the database environment and user under which the scheduler is to run.

The environment file must be copied to the \$HOME directory of the user selected in Step (1). It may be called anything, but a meaningful name may be `tdenv_TDPID_user` for a given Teradata scheduler.

Check the users .profile and database environment file to see the normal settings.

- o Replace all occurrences of `_HOME_` with the full pathname of your home directory.
- o Replace all occurrences of `_TDPID_` with the host name of the data warehouse database server, used by the scheduler as the database server name for Teradata load and unload utilities.
- o Replace all occurrences of `_BTEQDB_` with the host name or IP address of the data warehouse database server, used by the scheduler as the database server name/address for reading and writing WhereScape RED Metadata in Teradata (may be set to the same value as `_TDPID_`).
- o Replace `_USER_` with the data warehouse database user name.
- o Replace `_PASSWORD_` with the data warehouse database user password.
- o If using a Teradata Wallet String, comment out the first Password line and comment back in the second line containing `_WALLETSTRING_`. Replace all occurrences of `_WALLETSTRING_` with the data warehouse user wallet string.
- o Replace all occurrences of `_METABASE_` with the user or database where the metadata resides
- o Replace all occurrences of `_WORKDIR_` with the name of the directory that will be used as the work directory by default (e.g. `/tmp/`)

6. Setup crontab

Ascertain if there are any existing crontab entries, and if so save them to a file for re-inclusion later. (e.g. `crontab -l crontab -l >/tmp/my_crontab`).

Edit the crontab file and perform the following changes. Also check all entries and make sure you are happy with the times and actions:

- o Change all occurrences of `_HOME_` with the full pathname of the Unix users home directory.
- o Change all occurrences of the environment file name (oraenv or tdenv) to the name of the file created in step (4).
- o Remove comment markers from the beginning of the second line of code (the line containing this: `ws_sched_check_nnn.sh`).
- o Include any existing crontab entries as recorded above.

7. Initialize crontab entries


- o Load the crontab file into cron (e.g. `crontab crontab`).
- o Perform a crontab list to ensure it all looks OK (e.g. `crontab -l`).

8. Start Scheduler

Manually start the scheduler by issuing the `ws_sched_check_nnn.sh` script with the environment file name from step (4) as the parameter (e.g. `ws_sched_check_010.sh oraenv`) / (e.g. `ws_sched_check_600.sh tdenv`) / .

If the scheduler is not running it will be started. Execute the script a few more times to ensure that only one copy of the scheduler is started. Check that the scheduler is running by executing a `'ps -ef'` statement and checking that the `ws_sched_nnn.sh` process is present.

9. Start the Monitor process



Oracle only.

Manually start the monitor by issuing the `ws_mon_check_010.sh` script with the environment file name from step (4) as the parameter (e.g. `ws_mon_check_010.sh oraenv`). If the monitor is not running it will be started. Execute the script a few more times to ensure that only one copy of the scheduler is started. Check

that the monitor is running by executing a 'ps -ef' statement and checking that the ws_mon_010.sh process is present.

10. Test the Scheduler

Run a job from WhereScape RED and ensure that it works. In the event of the job not starting or going into and remaining in a pending state, then the following investigations should be undertaken:

- o Ensure all WhereScape procedures are compiled. Use the Validate metadata option in the Setup Administrator to confirm that all procedures are valid.
- o Review the job logs in \$HOME/wsl/sched/joblog.
- o Review the logs in \$HOME/wsl/sched/log.
- o Isolate the name of the job and locate the relevant files for this job in \$HOME/wsl/sched/job and \$HOME/wsl/sched/joblog if they exist. Mail these files together with the files in \$HOME/wsl/sched/log to support@WhereScape.com. It may be necessary to remove password references from the file(s) in \$HOME/wsl/sched/job.

Note:

It is possible to stop a Linux/UNIX Scheduler from within WhereScape RED. Refer to the *WhereScapeRED User Guide* or See the *Teradata WhereScapeRED User Guide* for further details.

Unix Scheduler setup for Hadoop loads using Oracle's Big Data Connectors

To set up the UNIX scheduler for Oracle loads from Hadoop using Oracle's Big Data connectors with OSCH and OLH, the following environment variables need to be edited in oraenv:

Example

```
export JAVA_HOME=/usr/lib/jvm/java-openjdk
export HADOOP_HOME=/home/oracle/hadoop-2.4.1
export PATH=$ORACLE_HOME/bin:$HADOOP_HOME/bin:$PATH
export JAVA_LIBRARY_PATH=$HADOOP_HOME/lib/native:$JAVA_LIBRARY_PATH
export HADOOP_COMMON_LIB_NATIVE_DIR=$HADOOP_HOME/lib/native
export HADOOP_OPTS="$HADOOP_OPTS -Djava.library.path=$HADOOP_HOME/lib/native"
```

For either OSCH or OLH, add one of the following to oraenv:

```
#OSCH
export OSCH_HOME=/home/oracle/orahdfs-3.1.0
export PATH=$OSCH_HOME/bin:$PATH
export HADOOP_CLASSPATH=$OSCH_HOME/jlib/*:$HADOOP_CLASSPATH

#OLH
export OLH_HOME=/home/oracle/oraloader-3.2.0-h2
export HADOOP_CLASSPATH=$OLH_HOME/jlib/*:$HADOOP_CLASSPATH
```

Notes:

Please restart the scheduler after you modified environment variables in oraenv.

The following Oracle directory objects need to be created with certain privileges:

OSCH

OSCH directory objects
 OSCH bin Directory
 OSCH External Tables Directory
 OSCH Log Directory

Example


```
CREATE DIRECTORY osch_bin_path AS '/opt/orahdfs-3.1.0/bin';
GRANT EXECUTE ON DIRECTORY osch_bin_path TO c##oschuser;
GRANT READ ON DIRECTORY osch_bin_path TO c##oschuser;
```

Notes:


```
CREATE DIRECTORY exttab_default_directory AS '/home/oracle/exttab';
GRANT READ ON DIRECTORY exttab_default_directory TO c##oschuser;
GRANT WRITE ON DIRECTORY exttab_default_directory TO c##oschuser;
CREATE DIRECTORY osch_log_path AS '/home/oracle/temp'
GRANT READ ON DIRECTORY osch_log_path TO c##oschuser;
GRANT WRITE ON DIRECTORY osch_log_path TO c##oschuser;
```

Maintaining the Windows Scheduler

- To maintain the Windows scheduler, click the **Scheduler** tab and then click **Scheduler Maintenance**.



- This option lists all currently active WhereScape schedulers. Right-click a scheduler name to display a context menu as follows:



The options are:

Option	Description
Configure	Enables the alteration of the service configuration. You can change the level of logging. The default is 2. Level 0 provides no log information and level 9 provides full debug. See Scheduler Creation for more detail.
Start	Starts a stopped scheduler. This action requires service control manager (SCM) privileges on the PC.
Stop	Stop a running scheduler. SCM privilege required.
Remove	Removes and deletes the scheduler. SCM required.

Option	Description
Service Account	By default, the scheduler will start in the system account. If you wish to change this, you can specify an account and password. However, you may have to remove the service and enter the account information when creating a new scheduler.
Manual Startup	Changes the startup profile (on PC startup) of the scheduler. The scheduler will not be automatically started when the PC starts and must be started manually. SCM required.
Automatic Startup	Sets the scheduler to start automatically when the PC starts. SCM required.
Disabled Startup	Sets the scheduler startup profile to disabled. No startup will occur unless the profile is changed to either Manual or Automatic. SCM required.
View Logfile	Displays the scheduler service log file. The level of logging is defined in the configuration of the scheduler.

Notes:

If an error occurs while a scheduled job is running, you should check the following:

- the audit log of the failed task, for any messages of type E or F.
- the audit log of the failed job, for any messages of type E or F.
- the scheduler log file for any error messages.
- the windows event logs, specifically the Application and System event logs, for any Error or Warning messages at the time of the job failure.

How to view and manage event logs depends on which version of Windows you are using. If you need further assistance, please contact support at support@wherescape.com.

BDA

Overview

WhereScape Big Data Adapter (BDA) is designed as an adapter to RED, focused on executing ELT related processing within the Hadoop/Hive eco-system.

This chapter attempts to guide users through the initial BDA setup, providing an overview of BDA, the prerequisites to operate it, step-by-step instructions to setup BDA. The setup of required connections and BDA operations is described in the *WhereScape RED User Guide*.

BDA is a java application and runs as a Tomcat webapp, with REST endpoints. BDA is simple to install, users only need to install RED, copy and extract the bda.tar.gz file from the Linux folder in RED's installation directory into the Linux system and execute the script. Before running the script, there are also other configuration settings that will need to be completed.

Prerequisites

To operate BDA, users must have the following prerequisites:

RED Environment


- Matching RED version
- bda.tar.gz file
- 32-bit or 64-bit Hive ODBC Driver (this is only required for accessing Hive tables)

BDA Environment

- Database specific JDBC drivers (Refer to [Adding JDBC drivers](#) for more details about the specific JDBC drivers required for each database type)
- Hadoop 2.7.1
- Sqoop 1.4.5
- Hive 1.1.0
- OpenSSL available on the Linux scheduler machine

BDA Diagram Overview

This diagram displays the operations performed by BDA and RED to integrate with Hive and Hadoop sources and using Sqoop to load to and from Target Databases.



- | | |
|---|--|
| (1) Configured in RED
Hive Connection object
BDA host and adapter | (4) Configured in RED
Source DB Connection object
JDBC Connection string |
| (2) Configured in bda.xml
jdbc/REDMeta property | (5) Configured in RED
Target DB Connection Object
JDBC Connection String |
| (3) Configured in RED
Hive Connection object
JDBC Connection string | |

How to set up BDA

Step-by-step instructions to set up BDA

Below is a sample step by step instruction on how to set up BDA, please note that you may have or you may choose to have different settings than the ones on the examples below.

1. From your WhereScape RED directory, go to the Linux folder and copy the bda.tar.gz file into your Linux system.
2. In your Linux system, create a folder to install BDA, in this example we are installing it the \$HOME/bda folder.
3. Unzip the bda.tar.gz file to \$HOME/bda folder.
4. Copy \$HOME/bda/conf/bdaenv to \$HOME and edit it according to your environment. In the example below, the file is configured for a SQL Server environment.

```

# WS_BDA_HTTP_PORT
#
# The TCP port number on which the BDA server will listen. This must be
# set to a port that is unused on this host and must match the BDA
# Server configuration in RED.
WS_BDA_HTTP_PORT=8080

# WS_BDA_JOB_WORKDIR
#
# The directory to write temporary scripts and other working files
# needed while executing tasks. If this directory exists, it must be
# writable by the user running the BDA Server; it will be created if
# it doesn't exist. Each running BDA Server environment requires a
# unique work directory; the use of $env_name in the default value for
# this variable ensures this.
WS_BDA_JOB_WORKDIR=$WS_BDA_ROOT_DIR/work/$env_name

# WS_BDA_REPOSITORY_TYPE
#
# The type of RDBMS used to host the metadata repository. Must be one
# of the following:
#
# SQLServer
# Oracle
# Teradata
# DB2

# WS_BDA_REPOSITORY_DRIVER
# WS_BDA_REPOSITORY_URL
# WS_BDA_REPOSITORY_USER
# WS_BDA_REPOSITORY_PWD
#
# These define the JDBC connection parameters used to connect to the
# RED metadata repository.

# Example for SQL Server metadata repository
WS_BDA_REPOSITORY_TYPE=SQLServer
WS_BDA_REPOSITORY_DRIVER=com.microsoft.sqlserver.jdbc.SQLServerDriver
WS_BDA_REPOSITORY_URL="jdbc:sqlserver://192.168.60.101:1433;databaseName=wsldemo"
WS_BDA_REPOSITORY_USER=demo_user
WS_BDA_REPOSITORY_PWD=password

# Example for Teradata metadata repository
# WS_BDA_REPOSITORY_TYPE=Teradata
# WS_BDA_REPOSITORY_DRIVER=com.teradata.jdbc.TeraDriver
# WS_BDA_REPOSITORY_URL="jdbc:teradata://10.10.10.10/DATABASE=DW,DBS_PORT=1025"
# WS_BDA_REPOSITORY_USER=
# WS_BDA_REPOSITORY_PWD=

# Example for Oracle metadata repository
# WS_BDA_REPOSITORY_TYPE=Oracle
# WS_BDA_REPOSITORY_DRIVER=oracle.jdbc.driver.OracleDriver
# WS_BDA_REPOSITORY_URL="jdbc:oracle:thin:@10.10.10.10:1521:orcl"
# WS_BDA_REPOSITORY_USER=
# WS_BDA_REPOSITORY_PWD=

```

5. Copy any required JDBC driver JARs into bda/lib.
6. Start BDA by running:

```
$HOME/bda/bin/ws_bda.sh start bdaenv
```

7. To Start BDA run:

```
$HOME/bda/bin/ws_bda.sh stop bdaenv
```


8. To change configuration:

```
Edit $HOME/bdaenv
```

```
Run $HOME/bda/bin/ws_bda.sh restart bdaenv
```

9. To upgrade BD:
 - Stop BDA
 - Copy the new **bda.tar.gz** file to the Linux system and extract it to \$HOME/bda folder
 - Start BDA

Sample BDA Setup



Adding JDBC Drivers

To add JDBC drivers:

1. Download the required JDBC driver for your specific database type:
 - o **ojdbc7.jar** for Oracle databases
 - o **sqljdbc4.jar** for SQL Server databases
 - o **terajdbc4.jar** and **tdgssconfig.jar** for Teradata databases
2. Add the required JDBC driver jar files to the relevant lib folders, such as \$HOME/bda/lib or sqoop/lib .

Example:

To load from either SQL, Oracle or Teradata, download the relevant JDBC driver(s) and copy the jar files to the bda/lib directory and Sqoop's lib directory.

On the Hortonworks sandbox and Cloudera quickstart virtual machines the sqoop library directory is /usr/lib/sqoop/lib .

Testing the BDA Setup

To test the BDA setup:

- Type the bda URL in your browser, for example: **http://192.168.60.201:8080/bda/rest/v1/admin/version**.
 - o The test will confirm that BDA is installed and configured correctly if the message displayed on the browser is your BDA version.




Note:

This doesn't display properly when using Internet Explorer®.
Microsoft® Edge, Google Chrome™ or Mozilla® Firefox® all display this correctly.

After completing the Hive connection setup described in the Hive connection topics in the RED, you can test the BDA connection from RED.

If the BDA server(s) are properly set up in RED, you can see the BDA Server versions configured in Hive connection objects by clicking in **Help > About WhereScape RED**.

If there are any messages displayed in this window, please refer to [Troubleshooting](#) for details.

**Important:**

A Hive connection must exist before BDA settings (**Connection > Properties > Big Data Adapter Settings**) appear in other database connections.

Configuring Kerberos for a secure use with BDA


To configure Kerberos for use with BDA, users need to do the following configuration steps:

1. Download the Kerberos Windows client (<http://web.mit.edu/kerberos/dist/>) and configure it using the Kerberos KDC.

Tip:

If necessary, manual changes for a Kerberos configuration in Windows can be made in the configuration file `C:\ProgramData\MIT\Kerberos5\krb5.ini`. In some installations where this file is not found, please add the system variable `KRB5_CONFIG=C:\ProgramData\MIT\Kerberos5\krb5.ini`.

2. Check your `KRB5CCNAME` environment variable; for example, `C:\temp\krb5cache`.



Notes:

- krb5cache is a regular file (not a directory) managed by the Kerberos software and should not be created by the user.
- If you change this variable, you will need to restart your computer to ensure MIT Kerberos for Windows uses this setting.

3. Cloudera Hive Configuration Example.

Note:

The following example is based on Cloudera Hive with impersonation enabled. Please refer to the vendor documentation for your Hive distribution to configure Kerberos in your environment.

Configure your Hive ODBC connection by downloading a Hive ODBC client, e.g. HortonWorks or Cloudera, and configure it to use Kerberos authentication as shown in the example below.

Cloudera ODBC Driver for Apache Hive DSN Setup

Data Source Name: cloudera_hive

Description: |

Hive Server Type: Hive Server 2

Service Discovery Mode: No Service Discovery

Host(s): 10.2.5.84

Port: 10000

Database: default

ZooKeeper Namespace:

Authentication

Mechanism: Kerberos

Realm: CLOUDERA

Host FQDN: quickstart.cloudera

Service Name: hive

User Name:

Password:

Save Password (Encrypted)

Delegation UID:

Thrift Transport: SASL

HTTP Options

SSL Options

Advanced Options...

Logging Options...

v2.5.17.1000 (32 bit)

Test OK Cancel

- In RED, update your JDBC connection string for your relevant connections.

The JDBC connection string for WhereScape RED connections to a Hive database needs to be updated to reflect the secured server where the principal in the connection string must be the HiveServer2-Kerberos-Principal:

```
example:
jdbc:hive2://quickstart.cloudera:10000/default;principal=hive/quickstart.cloudera@CLOUDERA;
```

- BDA then needs to be changed to connect to a Kerberos secured environment. The configuration parameters are the following options included in the bdaenv file:

```
#####
# Kerberos Authentication
#####

# Example configuration for a Kerberos-secured cluster
# WS_BDA_HADOOP_SECURITY_AUTHENTICATION=kerberos
# WS_BDA_HADOOP_SECURITY_PRINCIPAL=hive/quickstart.cloudera@CLOUDERA
# WS_BDA_HADOOP_SECURITY_KEYTAB=/etc/hive/conf/hive.keytab
```

6. Depending on the cluster configuration, there are two options with and without proxy users enabled.

The proxy option is the preferred option because this enables BDA to use any valid Kerberos principal instead of the hive super-user, in general hive/quickstart.cloudera@CLOUDERA. A sample configuration using a user defined principal is as follows:

```
WS_BDA_HADOOP_SECURITY_AUTHENTICATION =kerberos
WS_BDA_HADOOP_SECURITY_PRINCIPAL =bda@CLOUDERA
WS_BDA_HADOOP_SECURITY_KEYTAB =/home/bda/bda.keytab
```

If you need to access a cluster without proxy users enabled, you can use following configuration:

```
WS_BDA_HADOOP_SECURITY_AUTHENTICATION =kerberos
WS_BDA_HADOOP_SECURITY_PRINCIPAL =hive/quickstart.cloudera@CLOUDERA
WS_BDA_HADOOP_SECURITY_KEYTAB =/etc/hive/conf/hive.keytab
```

Note:

The last option for the keytab file assumes that the file `/etc/hive/conf/hive.keytab` exists and is readable for the user running the Tomcat service. In a Cloudera cluster using Cloudera Manager, keytab files are generated and stored in several local directories. One way to find the keytab file is to use the find command on the command shell: `find / -name hive.keytab -print`

and copy the corresponding file to the destination folder. Also, you will need to repeat this step after each password change of the principal "hive" in the Cloudera Manager.

Hadoop on a UNIX shell

For browsing Hadoop HDFS and loading data from Hadoop HDFS, WhereScape RED establishes a connection to the Linux server via a secure shell. Although some ssh-clients allow ticket forwarding for Kerberos this option is not available for PuTTY psexec. The easiest method is to create a keytab file that is readable only for the session user and to add the kinit command to obtain a Kerberos ticket at log-on time.

```
e.g.: add "kinit cloudera@CLOUDERA -k -t ~/cloudera.keytab" to
/home/cloudera/.bashrc.
```

Secured Hadoop and Scheduler

Apart from ODBC loads into Hive tables, all Kerberos authentications are performed on the Hadoop server side and, therefore, are independent of the invocation method, interactive or scheduler.

For ODBC loads, the service user running the scheduler needs to provide a valid ticket for a Kerberos principal. Because the ticket must be renewed automatically, a keytab file for this user needs to be provided on the server running the WhereScape RED scheduler. For instance, the Dos-shell command "kinit" can be run periodically as a Windows scheduled task to renew a ticket without user interaction:

```
e.g.: kinit -k -t C:\Users\ServiceUser\cloudera.keytab cloudera@CLOUDERA
```

Note:

The keytab file should be readable to the service user only.

Troubleshooting

BDA

If there are any issues with your setup, you can look into the log files.

- To check if BDA is working, enter the following URL on your browser:

<http://192.168.60.201:8080/bda/rest/v1/admin/version> or log in to RED and check the **Help > About WhereScape RED > BDA Server(s)**.

For some failed operations, the output in RED contains error messages. If you experience any further issues, please check if each of the components are working by executing the following commands below on the Linux server:

Hadoop

To check if HDFS is running, run the following command line on the Linux server.

```
wsldemo@suse-bda-1:~/bda> hdfs dfs -ls /user
```

Hive

To check if you can connect to Hive, run the following command line on the Linux server. Use the same JDBC connection string that has been defined in your Hive connection.

```
wsldemo@suse-bda-1:~/bda> beeline
Beeline version 1.2.1 by Apache Hive
beeline> !connect jdbc:hive2://localhost:10000
Connecting to jdbc:hive2://localhost:10000
Enter username for jdbc:hive2://localhost:10000: wsldemo
Enter password for jdbc:hive2://localhost:10000: *****
```

Sqoop


Using the following sqoop command line tool, you can test if sqoop is working. Use the same JDBC connection string that has been defined in your connection.

```
wsldemo@suse-bda-1:~/bda> sqoop eval --connect
'jdbc:teradata://192.168.60.100/DATABASE=wslrepo,DBS_PORT=1025' --driver
'com.teradata.jdbc.TeraDriver' --username 'wsldemo' --password 'password' --query 'SELECT 1'
```

Languages

The Languages component of **WhereScape's Setup Administrator** enables you to create a Language file or to load a Language File into RED.

1. Click on the **Languages** menu item in the command bar at the top of the screen.
 - o Click any of the options under this level to action them. The **Languages** menu is as follows:




- o The **Load Languages** - option lists the Language files that have been created. A file can be selected and loaded into the target Metadata Repository. Refer to [Loading Languages](#) for details.
- o The **Create Language File** - option enables you to create a Language file for a particular Metadata Repository. A translator is needed to replace the English definitions in the file with the translations relevant to the chosen language. Refer to [Creating a Language File](#) for details.
- o The **Change Languages Directory** - option enables you to change the language directory. Refer to [Changing the Languages Directory](#) for details.

Loading Languages

Note:

Before you install a language, you first need to logon to the repository in RED; go to **Tools/Language Options** and add the language.

1. Click the **Languages** menu at the top of the screen, then choose **Load Languages**.



2. The **Load Languages** menu option lists the Language Files available.
 - o Right-click a particular file and select **Install Language**.

Oracle	File	Language	Skip Existing	Skip Empty	Source ODBC Connection
Metadata Repository	lang_Original	Original	True	True	WsiWarehouse

--


You are then be prompted to logon to the required metadata repository and to select the Language to be updated in RED.

The results are shown in the middle pane.

Creating a Language File

To create a language file:

1. Click the **Languages** menu at the top of the screen.
 - o Select the **Create Language File** option.



2. You are prompted to logon to the required metadata repository. Language Files are applied to a specific metadata repository.

Once logged on, you are prompted for:

- o The **Language** - select from the drop-down list. Select a Language or choose **Original** to create a Language file containing the original values.
- o The **entries to exclude** from the extract.
- o The **file delimiter**, translation prefix and translation format.
- o The **file delimiter** provides an easy means of breaking up the file after extract.
- o The **translation prefix** must be something that will NEVER appear in the data itself. This is used to identify the start/end of any given field translation.

Language Extract [X]

Language: [Dropdown]

Language: Select the language to be extracted. You can choose 'original' to extract the base values rather than any specific translations.

Language: Original [Dropdown]

Exclusions:

Exclude language of type: True [Dropdown]

Exclude if no current translation: (original value must be empty) True [Dropdown]

Formatting:

Delimiter: = [Dropdown]

Translation prefix: {Translation} [Dropdown]

Translation format: 1 [Dropdown]

Example:

{Translation}FACT[fact_budget]->COLUMN[quantity].[DESC]=Quantity of product sold (i.e. number of product units).

Other:

Return replacement: [Dropdown]

File Mode: UTF-8 [Dropdown]

[OK] [Cancel]


A Language extraction file is then created and saved into **C:\ProgramData\RED\Language**.

A translator is needed to replace the English definitions in the file with the translations relevant to the chosen language.


Changing the Languages Directory

To change the languages directory:

1. Click on the **Languages** menu item in the command bar at the top of the screen and select **Change Languages Directory**.



2. Browse and select a new languages directory.




Tools


Start/Stop logging

In **WhereScape Administrator**, users have the option of logging all output to a file by selecting the **Start logging** function in the **Tools** menu.


1. To starting logging output from WhereScape Administrator, click on **Tools > Start logging** in the top bar.



2. When this option is selected, users are prompted to create a file in a specified location. Once this is done, all the output from WhereScape Administrator starts getting logged to that file.



3. To cancel logging, click **Tools > Stop logging**.



RED Command Line Interface

WhereScape RED provides command line interface applications that you can use to perform different tasks or execute functions and operations outside the RED GUI.

- [RED Client Command Line](#)
- [RED Setup Administrator Command Line](#)

RED Setup Administrator Command Line (adm.exe)

The RED Setup Administrator command line interface enables you to execute commands to :

- Quickly deploy a WhereScape RED application to create and populate a data warehouse
- Quickly create a RED repository with the required metadata tables
- Quickly load a file that contains language data into RED
- Quickly validate a RED repository and its metadata tables
- Quickly connect to a tutorial database to use in RED
- Install and configure a Windows scheduler for RED
- Deploy a RED application

The following is a sample Windows Command Prompt that displays the help for RED Setup Administrator (**adm.exe**) arguments.

```

C:\Program Files (x86)\WhereScape\WS_Classic>adm -h

C:\Program Files (x86)\WhereScape\WS_Classic>
General Arguments:
-h [ --help ]           Show this message
--quick-start          Quick start. -QS can be used as well.
--quick-app            Quick application. -QA can be used as well.
--quick-repo           Quick repository. -QR can be used as well.
--quick-lang           Quick language. -QL can be used as well.
--quick-validate       Quick validate. -QV can be used as well.
--quick-tutorial       Quick tutorial. -QT can be used as well.
--win-scheduler        Windows scheduler. -WS can be used as well.
--deploy-app           Deploy application. /AL can be used as well.
--stay-open            The application will stay open after running its task. /SO can be used as well.

Metadata Repository Arguments:
--meta-dsn arg         ODBC DSN of the metadata repository. /SN can be used as well.
-a [ --meta-dsn-arch ] arg (=32) The architecture of the ODBC DSN. Valid values are 32 and 64. Defaults to 32 if not specified.
--meta-user-name arg   Username for the ODBC DSN. /SL can be used as well.
--meta-password arg    Password for the ODBC DSN. /SP can be used as well.

Quick Application Arguments:
--instance-name arg    Instance name of the SQL Server RDBMS to connect to. -SS can be used as well.
--app-id-file-name arg Path name to the deployment application's ID file. -AN can be used as well.
--app-dir arg          Path name to the directory the deployment application's file are within -AD can be
  
```

RED Setup Administrator Command Line Arguments

The following describe the command line arguments that can be used in RED Setup Administrator (**adm.exe**).

Description	Argument long name	Argument short name
Display the RED arguments. Note: No other arguments required.	--help	-h or /h
Quick start Note: No other arguments required.	--quick-start	-QS or /QS
Quick application Note: Must have other arguments, refer to <u>Quick Application</u> .	--quick-app	-QA or /QA
Quick repository Note: Must have other arguments, refer to <u>Quick Repository</u> .	--quick-repo	-QR or /QR
Quick language Note: Must have other arguments, refer to <u>Quick Language</u> .	--quick-lang	-QL or /QL
Quick validate Note: Must have other arguments, refer to <u>Quick Validate</u> .	--quick-validate	-QV or /QV
Quick tutorial Note: Must have other arguments, refer to <u>Quick Tutorial</u> .	--quick-tutorial	-QT or /QT
Windows scheduler Note: Must have other arguments, refer to <u>Windows Scheduler</u> .	--win-scheduler	-WS or /WS
Deploy application Note: Must have other arguments, refer to <u>Deploy Application</u> .	--deploy-app	-AL or /AL
Stay open Notes: <ul style="list-style-type: none"> • Use to make Setup Administrator remain open, after the application has been created. • Relevant for -AL LOAD option. • Relevant for -QA, -QR, -WS, -QL and -QV application switch options. 	--stay-open	-SO or /SO

Note:

When `--quick-start (-QS or /QS)` is specified, then no other parameters are required.

The succeeding sections outline how the arguments are used.

Quick Application

The following describe the relevant command line arguments for quick application (`--quick-app` or `-QA`):

Description	Argument long name	Argument short name
Instance name	<code>--instance-name <name></code>	<code>-SS <name></code> or <code>/SS <name></code>
New repository name	<code>--meta-dsn <name></code>	<code>-SN <name></code> or <code>/SN <name></code>
Database login name	<code>--meta-user-name <name></code>	<code>-SL <name></code> or <code>/SL <name></code>
Database password	<code>--meta-password <password></code>	<code>-SP <password></code> or <code>/SP <password></code>
Application ID file name	<code>--app-id-file-name <name></code>	<code>-AN <file name></code> or <code>/AN <name></code>
Application file's directory	<code>--app-dir <path name></code>	<code>-AD <directory name></code> or <code>/AD <name></code>
Application load instance	<code>--app-instance <name></code>	<code>-LI <name></code> or <code>/LI <name></code>
Application trusted flag	<code>--app-trusted</code>	<code>-LT</code> or <code>/LT</code>
Application ODBC DSN	<code>--app-meta-dsn <name></code>	<code>-LD <name></code> or <code>/LD <name></code>
ODBC DSN architecture	<code>--meta-dsn-arch <32 64></code>	<code>-a <32 64></code> or <code>/a <32 64></code>
Application load database	<code>--app-db-name <name></code>	<code>-LN <name></code> or <code>/LN <name></code>
Application job name	<code>--app-job-name <name></code>	<code>-JN <name></code> or <code>/JN <name></code>
Datawarehouse connection name	<code>--dw-con-name <name></code>	<code>-DC <name></code> or <code>/DC <name></code>
MSAS cube connection name	<code>--msas-con-name <name></code>	<code>-CC <name></code> or <code>/CC <name></code>
MSAS cube database name	<code>--msas-db-name <name></code>	<code>-CD <name></code> or <code>/CD <name></code>
Scheduler login name	<code>--sched-login-name <name></code>	<code>-ML <name></code> or <code>/ML <name></code>
Scheduler password	<code>--sched-password <password></code>	<code>-MP <password></code> or <code>/MP <password></code>

Note:

Refer to [SQL Server Quick Application](#) for details.

Quick Repository

The following describe the relevant command line arguments for quick repository (`--quick-repo` or `-QR`):

Description	Argument long name	Argument short name
ODBC DSN	<code>--meta-dsn <name></code>	<code>-SN <name></code> or <code>/SN <name></code>
ODBC DSN architecture	<code>--meta-dsn-arch <32 64></code>	<code>-a <32 64></code> or <code>/a <32 64></code>
ODBC login name	<code>--meta-user-name <name></code>	<code>-SL <name></code> or <code>/SL <name></code>
ODBC password	<code>--meta-password <password></code>	<code>-SP <password></code> or <code>/SP</code>

Description	Argument long name	Argument short name
		<password>
TDPID	--tdpid <id>	-DI <name> or /DI <name>
Dimension tablespace	--dim-space <name>	-DS <name> or /DS <name>
Index tablespace	--index-space <name>	-IS <name> or /IS <name>
Metadata tablespace	--meta-space <name>	-MS <name> or /MS <name>

Note:

Refer to [SQL Server Quick Application](#) for details.

Quick Language

The following describe the relevant command line arguments for quick language (--quick-lang or -QL):

Description	Argument long name	Argument short name
ODBC DSN	--meta-dsn <name>	-SN <name> or /SN <name>
ODBC DSN architecture	--meta-dsn-arch <32 64>	-a <32 64> or /a <32 64>
ODBC login name	--meta-user-name <name>	-SL <name> or /SL <name>
ODBC password	--meta-password <password>	-SP <password> or /SP <password>
Language file	--lang-file-name <name>	-LF <path name> or /LF <path name>
Add language if absent	--add-lang	-Add or /ADD

Note:

Refer to [Languages](#) for details.

Quick Validate

The following describe the relevant command line arguments for quick validate (--quick-validate or -QV):

Description	Argument long name	Argument short name
ODBC DSN	--meta-dsn <name>	-SN <name> or /SN <name>
ODBC DSN architecture	--meta-dsn-arch <32 64>	-a <32 64> or /a <32 64>
ODBC login name	--meta-user-name <name>	-SL <name> or /SL <name>
ODBC password	--meta-password <password>	-SP <password> or /SP <password>
Dimension tablespace	--dim-space <name>	-DS <name> or /DS <name>
Index tablespace	--index-space <name>	-IS <name> or /IS <name>
Metadata tablespace	--meta-space <name>	-MS <name> or /MS <name>

Note:

Refer to [Validating a Metadata Repository using the Command Line](#) for details.

Quick Tutorial

The following describe the relevant command line arguments for quick tutorial (--quick-tutorial or -QT):

Description	Argument long name	Argument short name
ODBC DSN	--meta-dsn <name>	-SN <name> or /SN <name>
ODBC DSN architecture	--meta-dsn-arch <32 64>	-a <32 64> or /a <32 64>
ODBC login name	--meta-user-name <name>	-SL <name> or /SL <name>
ODBC password	--meta-password <password>	-SP <password> or /SP <password>

Note:

Refer to [Tutorial Data](#) for details.

Deploy Application

The following describe the relevant command line arguments for deploy application (--deploy-app or -AL):

Description	Argument long name	Argument short name
Application ID file name	--app-id-file-name <path name>	-AF <file name> or /AF <name>
Application parameter file name	--app-param-file-name <path name>	-PF <file name> or /PF <name>
Log file name	--log-file-name <path name>	-LF <path name> or /LF <path name>

Note:

Refer to [Creating and Loading Applications from the Command Line](#) for details.

Windows Scheduler

The following describe the relevant command line arguments for Windows scheduler (--win-scheduler or -WS):

Description	Argument long name	Argument short name
Scheduler name	--sched-name <name>	-ID <name> or /ID <name>
ODBC DSN	--meta-dsn <name>	-SN <name> or /SN <name>
ODBC DSN architecture	--meta-dsn-arch <32 64>	-a <32 64> or /a <32 64>
ODBC login name	--meta-user-name <name>	-SL <name> or /SL <name>
ODBC password	--meta-password <password>	-SP <password> or /SP <password>

Description	Argument long name	Argument short name
Metadata schema/database	--meta-database <name>	-MS <name> or /MS <name>
Service login name	--service-user-name <name>	-LN <name> or /LN <name>
Internal scheduler name	--int-sched-name <name>	-IN <name> or /IN <name>
Log level	--log-level <number>	-LL <number> or /LL <name>
Polling interval	--poll-interval <number>	-PI <number> or /PI <name>
Work directory	--work-dir <path name>	-WD <path name> or /WD <path name>
Log file name	--log-file-name <name>	-WL <path name> or /WL <path name>
TNS name	--tns-name <name>	-TN <name> or /TN <name>
Service password	--service-password <password>	-LP <password> or /LP <password>
Scheduler load type Notes: <ul style="list-style-type: none"> If omitted, the scheduler load type defaults to ODBC. The legacy option DL can be used to set only 32 bit OCI load type. 	--sched-load-type <ODBC OracleOCI OracleOCI64>	-DL or /DL is equivalent to --sched-load-type "OracleOCI"

Note:

Refer to [Installing a Windows Scheduler](#) for details.

RED Client Command Line (med.exe)

The RED Client command line interface enables you to execute commands to:

- Generate documentation in batch
- Create and deploy applications in batch
- Perform start up tasks for a new metadata repository

The following is a sample Windows Command Prompt that displays the help for RED Client (**med.exe**) arguments.

```

Command Prompt

C:\Program Files (x86)\WhereScape\WS_Classic>med -h

C:\Program Files (x86)\WhereScape\WS_Classic>
General Arguments:
-h [ --help ]           Display this message
--create-docs           Create documentation. /BD can be used as
                        well.
--create-deploy-app     Create a deployment application. /BA can be
                        used as well.
--new-meta-repo         Perform start up tasks for a new metadata
                        repository. -NEW can be used as well.

Metadata Repository Arguments:
-c [ --meta-dsn ] arg   ODBC DSN of the metadata repository
-a [ --meta-dsn-arch ] arg (=32) The architecture of the ODBC DSN. Valid
                                values are 32 and 64. Defaults to 32 if not
                                specified.
-u [ --meta-user-name ] arg Username for the ODBC DSN
-p [ --meta-password ] arg Password for the ODBC DSN
-m [ --meta-database ] arg Database name of the metadata repository
-n [ --red-user-name ] arg The RED user name to use

Documentation Arguments:
-g [ --group-name ] arg Name of a group to create documentation for
-d [ --output-dir ] arg Output directory to store generated files
                        into
-s [ --num-source-hops ] arg Maximum number of source hops to recurse
-i [ --no-impact-analysis ] If specified then the impact analysis

```

RED Client Command Line Arguments

The following describe the command line arguments that can be used in RED Client (**med.exe**) arguments.

Description	Argument long name	Argument short name
Display the RED arguments. Note: No other arguments required.	--help	-h or /h
Batch documentation create. Note: Must have other arguments, refer to Batch Documentation Creation in the RED User Guide.	--create-docs	-BD or /BD
Batch deployment application create. Note: Must have other arguments, refer to Batch Deployment Application Creation in the RED User Guide.	--create-deploy-app	-BA or /BA
First start with a new repository. Note: Must have other arguments, refer to New Metadata Repository Start up Task Creation in the RED User Guide.	--new-meta-repo	-NEW or /NEW

Description	Argument long name	Argument short name
Group name Note: All objects included, if group name is not specified.	--group-name <name>	-G or /G
Multiple use: Output directory or Database schema.	--output-dir <path name> or <db_schema>	-D or /D
Number of processes/ hops in the source diagrams.	--num-source-hops <number>	-S or /S
Disable impact analysis	--no-impact-analysis	-I or /I-
ODBC DSN	--meta-dsn <name>	-O or /O
ODBC user name	--meta-user-name <name>	-L or /L
ODBC DSN architecture	--meta-dsn-arch <32 64>	-A or /A
ODBC username	--meta-user-name <name>	-U or /U
ODBC password	--meta-password <password>	-P or /P
Connection name	--meta-dsn <name>	-C or /C
Metadata database Note: Only used in Teradata	--meta-database <name>	-M or /M
Session user name	--red-user-name <name>	-N or /N
Application ID number	--app-number <name>	-I or /I
Application version number	--app-version <number>	-V or /V
Application ID file name	--app-file-name <path name>	-AF or /AF
Remove connections	--remove-connections	-RC or /RC
Remove parameters	--remove-parameters	-RP or /RP
Remove scheduler jobs	--remove-jobs	-RJ or /RJ
Group name	--group-name <name>	-AG or /AG
Project name	--project-name <name>	-AP or /AP
All objects	--deploy-all	-ALL or /ALL

The succeeding sections outline how the arguments are used.

Batch Documentation Creation

The following describe the relevant command line arguments for creating batch documentation (--create-docs or -BD):

Description	Argument long name	Argument short name
ODBC DSN	--meta-dsn <name>	-C or /C
ODBC DSN architecture	--meta-dsn-arch <32 64>	-A or /A
ODBC user name	--meta-user-name <name>	-U or /U
ODBC password	--meta-password <password>	-P or /P
Metadata database Note: Only used in Teradata	--meta-database <name>	-M or /M
RED user name	--red-user-name <name>	-N or /N

Description	Argument long name	Argument short name
Group name Note: All objects included if group name is not specified.	--group-name <name>	-G or /G
Output directory	--output-dir <path name>	-D or /D
Number of processes/ hops in the source diagrams	--num-source-hops <number>	-S or /S
Disable impact analysis	--no-impact-analysis	-I- or /I-

Note:

Refer to the [Batch Documentation Creation](#) section of the RED User Guide for details.

Batch Deployment Application Creation

The following describe the relevant command line arguments for creating batch deployment application (--create-deploy-app or -BA):

Description	Argument long name	Argument short name
Output directory	--output-dir <path name>	-D or /D
ODBC DSN	--meta-dsn <name>	-C or /C
ODBC DSN architecture	--meta-dsn-arch <32 64>	-A or /A
ODBC user name	--meta-user-name <name>	-U or /U
ODBC password	--meta-password <password>	-P or /P
Metadata database Note: Only used in Teradata	--meta-database <name>	-M or /M
RED user name	--red-user-name <name>	-N or /N
Application ID number	--app-number <name>	-I or /I
Application version number	--app-version <number>	-V or /V
Application ID file name (e.g. app_id_XXX.wst)	--app-file-name <path name>	-AF or /AF
Remove connections	--remove-connections	-RC or /RC
Remove parameters	--remove-parameters	-RP or /RP
Remove scheduler jobs	--remove-jobs	-RJ or /RJ
Group name	--group-name <name>	-AG or /AG
Project name	--project-name <name>	-AP or /AP
All objects	--deploy-all	-ALL or /ALL

Note:

Refer to [Creating and Loading Applications from the Command Line](#) for details.

New Metadata Repository Start up Task Creation

The following describe the relevant command line arguments for creating start up tasks for a new metadata repository (--new-meta-repo or -NEW):

Description	Argument long name	Argument short name
ODBC DSN	--meta-dsn <name>	-O or /O
ODBC DSN architecture	--meta-dsn-arch <32 64>	-A or /A
ODBC user name	--meta-user-name <name>	-L or /L
Metadata database	--meta-database <name>	-D or /D

Copyright

Copyright © 2020 WhereScape, Inc. All rights reserved.

This document may be redistributed in its entirety and in this electronic or printed form only without permission; all other uses of this document and the information it contains require the explicit written permission of WhereScape, Inc.

Due to continued product development this information may change without notice. WhereScape, Inc. does not warrant that this document is error-free.

Trademark

WhereScape and WhereScape RED are trademarks or registered trademarks of WhereScape, Inc. Other brands or product names are trademarks or registered trademarks of their respective companies.

WhereScape, Inc.
10801 N Mopac Expressway
Building 1, Suite 100
Austin, Texas 78759

www.wherescape.com